


Art.-No.	VE	PG	EAN
812002517	1	116	4 008224 257244

INFRAcontrol 3D 140° AP IP54 attachment version infrared motion switch with two detection areas, detection angle: 140°, detection range: approx. 10m, switching time: 4-240 seconds, light threshold adjustable with slide switch: permanently OFF, automatic, permanently ON, 3-wire device for resistive and inductive loads, switching capacity: max. 2000W, 230V~, 50/60Hz, arctic-white

Technical data		812002517
Model	Movement sensor	
Mounting method	Surface mounted (plaster)	
Material	Plastic	
Material quality	Thermoplastic	
Surface protection	Untreated	
Surface finishing	Matt	
Colour	White	
Colour (user defined)	arctic white	
Degree of protection (IP)	IP54	
Voltage type	AC	
Constant light control	No	
HVAC-control	No	
Forced switch off	No	
Animal zone	No	
Creep-under protection	Yes	
Networkable	No	
Optimum mounting height	1.8m	
Staircase monitoring	No	
Bridging switch	No	
Max. transmission range sideways	10m	
Max. transmission range frontally	10m	
Diameter detection range on floor	10m	
Suitable for wireless transmission	No	
Remote operation	No	
Response value sensitivity adjustable	No	
Response value luminosity adjustable	Yes	
With signal unit	No	
Teach-function for response value luminosity	No	
Dim function with dimmer basic element	No	
Transparent	No	
Frequency	50Hz	
Nominal voltage	230V	



Technical data		812002517
Min. switch-on time	5s	
Max. duty cycle	4min	
Detection angle horizontal	140°	
Max. switching power	2000W	
Temperature	-25-70°C	
Max. starting current	10A	
Substation input	No	
With alarm function	No	