



Strip-Light LED

451158.002.1 | Linear luminaires



Ceiling and wall luminaires
4051859035763
LED
L 836, B 23, H 37



Very compact linear luminaire with rocker switch. Universally suitable for store lighting, vault lighting, kitchen and bathroom lighting. Base: plastic. Diffuser: transparent plastic, prismatic. Excellent light distribution thanks to prismatic cover. Suitable for Ceiling mounting, Wall (surface). Easy to mount with clips. Connecting cables for through-wiring without tools. Max. 12 luminaires can be mounted as a light channel. Included in delivery: 1.80 m power supply cable, 150 mm connecting cable, straight rigid coupling and 2 brackets each for wall and ceiling mounting. Suitable for mounting on or into furniture.

Colour

Colour white

Dimensions

Length L 836 mm
Width B 23 mm
Height H 37 mm
Weight 362 g

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Lifetime 25000 h (L70/B50)

Lighting technology

Beam Angle 176°/113°
Photobiological safety according to EN 62471 Risk group 0

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Colour temperature 1	4.000 K
System power 1	13 W
Rated luminous flux 1	1.250 lm
Glare evaluation UGR (4H 8H) 1	25,8
Luminaire efficacy 1	97 lm/W

Approbations

Type of Protection	IP 20
Protection Class	II
Glow Wire Test	750°C - 30 seconds
Impact Protection	IK02 (0,20 Joule)
Safety marks	F-mark, MM
Other Marks	WEEE mark
Energy efficiency class LED	A+
Energy class of included lamp	A+

Accessories

981457.002	Accessories L 1800 Power supply cable (Europlug with socket)
981462.002	Accessories L 160,
981464.002	Accessories L 300, Connecting cable
981466.002	Accessories L 600, Connecting cable
981467.002	Accessories L 900, Connecting cable
981470.002	Accessories L 47, B 47, H 42 Corner connectors