



# Triade LED

## 751141.004.1 | Surface mounted projector



Surface mounted projectors  
4051859093879  
LED  
L 600, B 89, H 178



LED spotlight for surface / track mounting in geometrical design for indoor applications. For general and wall lighting. Housing: aluminium extrusion profile, powder-coated. Vertical swivel range: 90°. Diffuser: plastic (polycarbonate), opal. Homogeneous and smooth light distribution. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Integral driver.

### Colour

Colour silver coloured

### Dimensions

Length L 600 mm  
Width B 89 mm  
Height H 178 mm  
Weight 1,72 kg

### Lamp

Lamp LED  
Colour temperature 4000K  
Colour rendering index (CRI) 80  
Colour consistency (McAdam) 4  
Lifetime 50000 h (L70/B10)

### Lighting technology

Beam Angle 88°/97°

### Electrical

|                                          |                          |
|------------------------------------------|--------------------------|
| Control gear                             | Converter                |
| Voltage                                  | 220 - 240 V / 50 - 60 Hz |
| Luminaires on B10A fuse                  | 17                       |
| Luminaires on B16A fuse                  | 28                       |
| Inrush current / inrush current duration | 53 A                     |
| Colour temperature 1                     | 4.000 K                  |
| System power 1                           | 36 W                     |
| Rated luminous flux 1                    | 3.100 lm                 |
| Glare evaluation UGR (4H 8H) 1           | 26,4                     |
| Luminaire efficacy 1                     | 87 lm/W                  |

### Approbations

|                               |                    |
|-------------------------------|--------------------|
| Type of Protection            | IP 20              |
| Protection Class              | I                  |
| Glow Wire Test                | 650°C - 30 seconds |
| Impact Protection             | IK02 (0,20 Joule)  |
| Safety marks                  | F-mark             |
| Other Marks                   | WEEE mark          |
| Energy efficiency class LED   | A+                 |
| Energy class of included lamp | A+                 |