



Flat Polymero Kreis Slim

312090.002.1 | Pendant luminaires



Pendant luminaires
4051859155737
LED
D 460, H 65



Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 55 mm. Diffuser: plastic (non-yellowing PMMA), opal. Diffuser fastening: patented push system. Homogeneous and smooth light distribution. Suitable for Pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request.

Colour

Colour white

Dimensions

Diameter D 460 mm
Height H 65 mm
Suspension length 200-1300 mm
Weight 4,54 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 83
Colour consistency (McAdam) 3
Lifetime 50000 h (L70/B10)

Lighting technology

Beam Angle 120°
Photobiological safety according to EN 62471 Risk group 1

Electrical

Control gear	Converter not necessary
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	84
Luminaires on B16A fuse	135
Luminaires on C10A fuse	84
Luminaires on C16A fuse	135
Inrush current / inrush current duration	0.22 A / 200 µs
System power 1	21 W
Rated luminous flux 1	1.750 lm
Glare evaluation UGR (4H 8H) 1	18,8
Luminaire efficacy 1	84 lm/W

Approbations

Type of Protection	IP 40
Protection Class	I
Glow Wire Test	650°C - 30 seconds
Impact Protection	IK03 (0,35 Joule)
Safety marks	F-mark
Other Marks	WEEE mark
Energy efficiency class LED	A+
Energy class of included lamp	A+