HVI LI 20 L7.5M SR5040 FSP500 GFK AL V2A (819 259)



Figure without obligation



Type Part No.	HVI LI 20 L7.5M SR5040 FSP500 GFK AL V2A 819 259
Material of supporting tube	GRP / Al
Length of supporting tube	5040 mm
Transport length	5040 mm
Material of air-termination tip	StSt
Length of air-termination tip	500 mm
Diameter Ø conductor	20 mm
Colour of conductor	grey
Material of conductor	Cu
RAL colour	similar to 7000
Cross section of core	19 mm²
Lightning current carrying capability (class / I_{imp})	H1 / 150 kA
Equivalent separation distance s (air)	≤ 45 cm
Material of insulation	PE
Material of sheath	PVC
Characteristics of sheath	UV stabilized and weather resistant
Connection diameter	10 mm
EB connection cable	strip StSt 4050 x 18 x 0.4 mm
Material of connection elements	StSt
Minimum order length	7.5 m
Max. gust wind speed	148 km/h
Max. free length	4940 mm
Min. clamping length	600 mm
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	10,99 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364256088
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.