# RBK 35 SQ (715 312)

- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator



Figure without obligation





Figure without obligation

| Type<br>Part No. | RBK 35 SQ<br>715 312 |
|---|---|
| For round pins Ø | 35 mm |
| Anti-rotation protection | PK1 |
| For cable cross-section Cu | 16 ... 150 $mm^2$ |
| Max. short-circuit current $I_k$ 0.5 s | 42.0 kA |
| Max. short-circuit current $I_k$ 1 s | 29.6 kA |
| Standard | EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087 |
| Temperature range | –25 °C ... +55 °C |
| Material (clamp body) | Copper alloy/gal Sn |
| Material (shaft) | Copper alloy/gal Sn |
| Material (pressure plate) | Copper alloy/gal Sn |
| Weight | 1,5 kg |
| Customs tariff number (Comb. Nomenclature EU) | 85359000 |
| GTIN | 4013364150386 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The clamps must have the same maximum short-circuit current as the earthing and short-circuiting cables!