IGA 24 IP54 (902 472)


- Easy visual inspection of the installed arresters through transparent door
- With integrated three-pole PE and twelve-pole N plug-in terminals
- With cable entry cover



Figure without obligation



Integrated plug-in terminal technology for PE and N conductors.



Dimension drawing IGA 24 IP54

Insulating enclosure for arresters with a capacity of 2x 12 modules; with integrated, elastic seal membrane for cable entry; ideally suited for feed-through wiring.

Type **Part No.**	**IGA 24 IP54** **902 472**
Degree of protection	IP 54
Type of cover	transparent door
Colour of enclosure	grey, RAL 7035
Number of cable entries	8x for cables Ø7-12 mm; 8x for cables Ø7-14 mm; 4x for cables Ø12-20 mm; 1x for cables Ø16.5-29 mm (top and bottom)
PE / N quantity x cross-section	6x 25 mm^2, 24x 4 mm^2,Cu
Capacity	24 modules (2x 12 modules), DIN 43880
Dimensions (W x H x D)	295 x 458 x 129 mm
Weight	2,39 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364108950
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.