


DGA AG BNC (929 043)


- Large-area contact surface for connecting gas discharge tubes
- Longevity due to minimum contact erosion at the inner conductor
- For installation in conformity with the lightning protection zone concept at the boundaries from $0_A - 1$ and higher



Figure without obligation



Basic circuit diagram DGA AG BNC



Dimension drawings DGA AG BNC

Arrester suitable for remote supply with exchangeable gas discharge tube. Long endurance due to minimum contact erosion resulting from the large-area contact surface of the gas discharge tube.

Type	DGA AG BNC
Part No.	929 043
SPD class	TYPE1
Max. continuous operating voltage (d.c.) (U_C)	180 V
Nominal current (I_L)	3.5 A
Max. transmission capacity	150 W
D1 Lightning impulse current (10/350 μ s) (I_{imp})	5 kA
C2 Nominal discharge current (8/20 μ s) (I_n)	20 kA
Voltage protection level for I_n C2 (U_P)	≤ 850 V
Frequency range	0-1 GHz
Insertion loss	< 0.1 dB
Return loss	≥ 19 dB
Characteristic impedance (Z)	50 ohms
Operating temperature range (T_U)	-40 °C ... +85 °C
Degree of protection	IP 20
Connection	BNC socket / BNC plug
Earthing via	bushing (Ø16.1 mm)
Enclosure material	brass, refined surface with trimetal plating
Colour	bare surface
Exchangeable gas discharge tube	yes
Test standards	IEC 61643-21 / EN 61643-21
Weight	90 g
Customs tariff number (Comb. Nomenclature EU)	85366910
GTIN	4013364091047
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.