UK 25 SQ (773 234)

- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator



Figure without obligation




Figure without obligation

*) Clamping range and maximum cable cross-section of universal clamps used for:

Fixed ball point Ø	Phase T pin collar width	Rd / Fl clamping range	Cable cross-section
20/25/30 mm	15/18 mm	20/30 mm	16 mm²
20/25/30 mm	15/18 mm	20/30 mm	25 mm²
20/25/30 mm	15/18 mm	20/30 mm	35 mm²
20/25/30 mm	15/18 mm	20/30 mm	50 mm²
20/25/30 mm	15/18 mm	20/30 mm	70 mm²
20/25/30 mm	15/18 mm	–	95 mm²
–/25/30 mm	–	–	120 mm²
–	–	–	150 mm²

Type Part No.	UK 25 SQ 773 234
For fixed ball point Ø	20 / 25 mm
For T pins with a collar width of	15 mm
Min. clamping range Rd / Fl	10 / 5 mm
Rd / Fl clamping range	20 mm
Anti-rotation protection	PK1
For cable cross-section Cu	16 ... 120*) mm²
Max. short-circuit current I_k 0.5 s	33.5 kA
Max. short-circuit current I_k 1 s	23.7 kA
Standard	EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087
Temperature range	–25 °C ... +55 °C
Material (clamp body)	Copper alloy/gal Sn
Material (shaft)	Copper alloy/gal Sn
Material (pressure plate)	St/gal Zn
Weight	661 g
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364114555
PU	1 pc(s)

*) See table for „Clamping range and maximum cable cross-section of universal clamps used for"

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The clamps must have the same maximum short-circuit current as the earthing and short-circuiting cables!