





- M12 sensor/actuator box, 8-way
- 5-pole (2 signals per contact)
- Cable length: 5, 10 and 25 m
- Green LED operating indicator
- Yellow LED status indicator
- incl. markers (10 pcs)
- incl. M12 protective caps (2 pcs)

Technical data	
Contact resistance (max.)	0.01 Ω
Supply voltage	10 ... 30 VDC; Rated voltage: 32 V ~ rms
Current carrying capacity (signal connections)	2 A
Current carrying capacity (supply connections)	9 A
Rated value of electrical isolation	500 V
Functionally separated potential groups	Kontakt/Kontakt
Insulation resistance	>10 ⁹ Ω
Signal characteristics	PNP
Indicators	LED (A, B) yellow: Signal status (2 x per contact); LED (U) green: Sensor/actuator box status



Connection data	
Connection technology: inputs/outputs	8 x M12 socket; 5-pole; incl. ground
Connection technology: trunk cable	1 x Fixed connecting cable
Length of connection cable	10 m
Strip length	100 mm / 3.94 inches
Wire colors	white, gray/pink, green, red/blue, yellow, white/green, gray, brown/green, pink, white/yellow, red, yellow/brown, black, white/gray, purple, gray/brown, green/yellow, brown, blue
Cable design	Wire cross-section: 0.34 mm ² ; Wire cross-section (2): 1 mm ²

Physical data	
Width	60 mm / 2.362 inches
Height	26 mm / 1.024 inches
Depth	152 mm / 5.984 inches

Mechanical data	
Mounting type	Screw mount
Weight	1613 g

Material data	
Housing material	PA 66 (UL 94 V0); RAL 7035; silicon and halogen free
Halogen-free	Yes
Sheathed cable diameter	9.7 mm
Bending radius	10 x cable diameter (min.) for flexible application
Material properties of the connections	Contact: CuSn, nickel base-coat plating and 0.8 µm gold-plated; Threaded bush: die-cast Zn, nickel-plated; Seal: Viton; 50 mating cycles
Sheath material	PUR
Sheathed cable color	black
Encapsulation	Fully encapsulated with conformal coating (UL 94 V0)

Environmental requirements	
Ambient temperature (operation)	-25 ... +80 °C
Ambient (operating) temperature (dynamic)	-5 ... +80 °C
Ambient (operating) temperature (static)	-40 ... +90 °C
Protection type	IP68
Note on protection type	72 h at a depth of 1 m under water per EN 60529 in the fully locked position with its plugs or protective caps
Pollution degree	3 per VDE 0110
Vibration resistance	per IEC 60068-2-6
Shock resistance	per IEC 60068-2-27

Commercial data	
eCl@ss 10.0	27-44-01-08
eCl@ss 9.0	27-44-01-08
ETIM 8.0	EC002585
ETIM 7.0	EC002585
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454028503
Customs tariff number	85366990990



Environmental Product Compliance	
CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	427ffd3a-66be-4b47-84b4-f50fa769690e
SCIP notification number (Belgium)	2477dc83-50c6-4ddf-b9b6-160c839362c6
SCIP notification number (Bulgaria)	2e238297-4662-460a-bc7a-8386af516888
SCIP notification number (Czech Republic)	b334c42b-bbf1-41ed-8e89-01afcced3fb8
SCIP notification number (Denmark)	f0283171-95f4-46cd-b42b-9297a7266dab
SCIP notification number (Finland)	08d782bb-1970-44a4-baca-71438edfddb9
SCIP notification number (France)	553b97ad-64f3-4dbf-b9cc-26b2331b19f9
SCIP notification number (Germany)	a3ff771e-b98d-4e5c-94c6-bd242f5dfb48
SCIP notification number (Hungary)	020e11ce-26b4-4ee5-9fa3-778ce5fb437d
SCIP notification number (Italy)	efcd3047-ed45-4394-9122-97b3b7e819f0
SCIP notification number (Netherlands)	baa30e06-c5e6-444d-be57-1c11ff1b9c47
SCIP notification number (Poland)	91038407-a329-4384-8a54-16fc4bb0c22a
SCIP notification number (Romania)	9218ea2b-46b9-42b2-b7f5-8f8163d18667
SCIP notification number (Sweden)	6d09b9c4-27b3-4ec3-9c7c-a9d7516ca2df

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
UL UL International Germany GmbH (ORDINARY LOCA- TIONS)	UL 508	E175199 Sec.5

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 757-285/000-010



Documentation

System Description
Sensor/Actuator Bo- xes – General Product Information

pdf
428.34 KB





CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 757-285/000-010	EPLAN Data Portal 757-285/000-010
	WSCAD Universe 757-285/000-010
	ZUKEN Portal 757-285/000-010

1 Compatible Products
1.1 Optional Accessories
1.1.1 Cover
1.1.1.1 Cover



[Item No.: 756-8102](#)
M12 protective cap; for unused sockets

1.1.2 Installation
1.1.2.1 Intermediate plate



[Item No.: 757-080](#)
Spacer module for sensor/actuator box; 8-way

1.1.3 Marking
1.1.3.1 Marking device



[Item No.: 210-110](#)
Fiber-tip pen

1.1.3.2 Marking strip



[Item No.: 757-011](#)
Marker card; not stretchable; snap-on type