

Datasheet

REGIOLUX

Category (ETIM):	Control unit+sensor
Type:	Switch signal Switching control devices-LC-BEG PD4-M-1C-GH-AP
Order number:	84506002100
Mains voltage:	230V / 50Hz
Certifications:	IP 20, protection class II, CE
Weight (net) (kg):	0.132
Dimensions LxWxH/DxH (mm):	98 x 63
mounting method:	Surface single mounting
EAN-number:	4020863269792
Commodity code:	85365080

LC-BEG PD4-M-1C-GH-AP • 84506002100



Light/presence sensor for ceiling surface mounting

Presence sensor, remote-controllable with oval and long-range monitoring area, specifically for high rise racking; automatic reading of the current light value; switching the lighting on and off and parameterisation of the presence sensor by remote control; high-performance relay, with inrush current limiter; sensor and power part in the same housing; can also be switched using pushbutton; monitoring area Ø44.00 m; 1 channel (light control); switching power 2300 W, $\cos\phi=1$; 1150 VA, $\cos\phi=0.5$; time setting 15 sec.-30 min. or pulse; brightness value - 10-2000 lx. A remote control (LC-BEG IR-PD4-GH) for operation of the control is also required. Expansion of the reception range using LC-BEG PD4-GH-AP is possible. Optional wire basket, IP54 base and cover strips.

Dimensions LxWxH/DxH (mm): 98 x 63
Certifications: IP 20, protection class II, CE

Regiolux GmbH
Type: LC-BEG PD4-M-1C-GH-AP
Article number: 84506002100
Product deep link: <http://www.regiolux.de/de/article/84506002100>