

Datasheet

REGIOLUX

Category (ETIM):	Control unit+sensor
Type:	DALI signal, Switch signal Compact control devices, Switching control devices-LC-BEG PD4-S-AP
Order number:	84506005100
Mains voltage:	230V / 50Hz
Certifications:	IP 54, protection class II, Indoor, CE
Weight (net) (kg):	0.202
Dimensions LxWxH/DxH (mm):	101 x 76
mounting method:	Surface single mounting
EAN-number:	4020863269914
Commodity code:	85365080

LC-BEG PD4-S-AP • 84506005100



Slave sensor presence for ceiling surface mounting

Presence sensor, slave sensor with circular and long-range monitoring area, surface mounting, for master/slave combination. Only one master for light switching is necessary; motion detection in all areas of the room possible with slave sensors; switching pulse to the master in the case of detected movement; recognition of the motion independent of ambient lighting; sensor and power part in the same housing; range in sitting position Ø 6.4 m, lateral Ø 24.0 m, frontal Ø 8.0 m. A master sensor for the operation of the control (LC-BEG PD4-M-AP) is also required. Optional wire basket, IP54 base and cover strips.

Dimensions LxWxH/DxH (mm): 101 x 76

Certifications: IP 54, protection class II, Indoor, CE

Regiolux GmbH

Type: LC-BEG PD4-S-AP

Article number: 84506005100

Product deep link: <http://www.regiolux.de/de/article/84506005100>