Datasheet


REGIOLUX

Category (ETIM):	Surface-mounted diffuser/surface-mounted luminaire
Type:	wotek-WKO LED
Order number:	21705314180
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver emergency light 3 hours (2 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	43
Ballast lumen factor BLF (emergency lighting mode):	5
Luminaire luminous flux (lm):	4700
lm/W:	109
Energy efficiency class:	A+
Impact resistance (IK rating):	IK02
Certifications:	IP 54, protection class I, D, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	4.03
Dimensions LxWxH/DxH (mm):	1510 x 120 x 90
Cable entry KE X/Y (mm):	30 / 0
mounting method:	Surface single mounting, Wall mounting IP44
EAN-number:	4020863325115
Commodity code:	94051098


wotek-WKO/1500 LED 4700lm 840 • vw • EM pack 3h • 21705314180




Lighting technology
Diffuser, opal-direct/indirect distribution
WKO/1500 LED 4700 lm 840




ηLB	100 %
lm/W	109
Φ ↓/↑	77 % / 23 %
UGR q/l	22.0 / 19.2



Surface-mounted diffuser/surface-mounted luminaire; Luminaire body made of sheet steel, with age-resistant PUR foam sealing in the circumferential edge and spring locks, cable entries on the top side of the housing. Housing colour traffic white RAL 9016; Direct light distribution using diffuser made of acrylic glass with opal colouring, with high corner strength and drawn from one piece, UV-resistant; With 3 hours emergency lighting battery. Inverter; batteries and LED as function control; Electrical connection and connection for emergency light using 5-pole connection terminal with plug-in contacts. Slotted discs and spacers are included for optimal ceiling adjustment.



Dimensions LxWxH/DxH (mm): 1510 x 120 x 90
Cable entry KE X/Y (mm): 30 / 0
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 4700
lm/W: 109
Operating device: Electronic driver emergency light 3 hours (2 pcs.)
System performance (W): 43
Ballast lumen factor BLF (emergency lighting mode): 5
Energy efficiency class: A+
Impact resistance (IK rating): IK02
Certifications: IP 54, protection class I, D, F, Indoor, CE



Regiolux GmbH
Type: wotek-WKO/1500 LED 4700 840 NL-B3 vw
Article number: 21705314180
Product deep link: http://www.regiolux.de/en/article/21705314180
5 year guarantee after registration on website.