# Datasheet


REGIOLUX

| | |
|---|---|
| Category (ETIM): | Surface-mounted diffuser/surface-mounted luminaire |
| Type: | wotek-WKO LED |
| Order number: | 21702014180 |
| Configuration: | Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10 |
| Operating device: | Electronic driver 230-240V/0Hz/50-60Hz (1 pcs.) |
| Mains voltage: | 230V / 50Hz |
| System performance (W): | 33 |
| Luminaire luminous flux (lm): | 3600 |
| lm/W: | 110 |
| Energy efficiency class: | A+ |
| Impact resistance (IK rating): | IK02 |
| Certifications: | IP 54, protection class I, D, F, Indoor, CE |
| Colour of the housing: | traffic white RAL 9016 |
| Weight (net) (kg): | 3.1 |
| Dimensions LxWxH/DxH (mm): | 1210 x 120 x 90 |
| Cable entry KE X/Y (mm): | 30 / 0 |
| mounting method: | Surface single mounting, Wall mounting IP44 |
| EAN-number: | 4020863323142 |
| Commodity code: | 94051098 |


**wotek-WKO/1200 LED 3600lm 840 • vw • EN 230-240V/0Hz/50-60Hz • 21702014180**




**Lighting technology**
Diffuser, opal-direct/indirect distribution
WKO/1200 LED 3600 lm 840



| | |
|---|---|
| ηLB | 100 % |
| lm/W | 110 |
| Φ ↓/↑ | 77 % / 23 % |
| UGR q/l | 21.9 / 19.0 |




Surface-mounted diffuser/surface-mounted luminaire; Luminaire body made of sheet steel, with age-resistant PUR foam sealing in the circumferential edge and spring locks, cable entries on the top side of the housing. Housing colour traffic white RAL 9016; Direct light distribution using diffuser made of acrylic glass with opal colouring, with high corner strength and drawn from one piece, UV-resistant; Electrical connection via 3-pole connection terminal with plug-in contacts. Slotted discs and spacers are included for optimal ceiling adjustment.




Dimensions LxWxH/DxH (mm): 1210 x 120 x 90
Cable entry KE X/Y (mm): 30 / 0
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3600
lm/W: 110
Operating device: Electronic driver 230-240V/0Hz/50-60Hz (1 pcs.)
System performance (W): 33
Energy efficiency class: A+
Impact resistance (IK rating): IK02
Certifications: IP 54, protection class I, D, F, Indoor, CE

Regiolux GmbH
Type: wotek-WKO/1200 LED 3600 840 ET 230-240V/0Hz/50-60Hz vw
Article number: 21702014180
Product deep link: http://www.regiolux.de/en/article/21702014180
5 year guarantee after registration on website.

