Datasheet

REGIOLUX

Category (ETIM):	Device mounts
Type:	Device mount IP20-SDGLK LED
Order number:	18230474100
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver emergency light 3 hours (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	40
Ballast lumen factor BLF (emergency lighting mode):	11.8
Luminaire luminous flux (lm):	5500
lm/W:	138
Energy efficiency class:	A++
Certifications:	IP 20, protection class I, F, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2.7
Dimensions LxWxH/DxH (mm):	1531 x 63 x 54
mounting method:	Mounting rail system mounting
EAN-number:	4020863308613
Commodity code:	94051098

SDGLK LED 5500lm 840 • vw • EM pack 3h • 18230474100



Lighting technology
Diffuser, frosted-direct/indirect distribution
SDGLK LED 5500 lm 840



ηLB	100 %
lm/W	138
Φ ↓/↑	84 % / 16 %
UGR q/l	24.2 / 22.8



Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Housing colour traffic white RAL 9016; Direct/indirect light distribution, frosted diffuser made of PMMA plastic with inner longitudinal prisms. Optically seamless light run. With 3 hours emergency light battery and integrated status indicator; three hours emergency light operation. Heat-resistant cables including permanently fixed 4-pole quick-mount plug connector with tool-free phase preselection and locating finger; one wire of the through-wiring can be used as unswitched charging phase using additional pole on the plug connector;

Dimensions LxWxH/DxH (mm): 1531 x 63 x 54
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 5500
lm/W: 138
Operating device: Electronic driver emergency light 3 hours (1 pcs.)
System performance (W): 40
Ballast lumen factor BLF (emergency lighting mode): 11.8
Energy efficiency class: A++
Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGLK LED 5500 840 NL-B3 vw
Article number: 18230474100
Product deep link: http://www.regiolux.de/de/article/18230474100
5 year guarantee after registration on website.