Datasheet

REGIOLUX

Category (ETIM):	Device mount IP 54
Type:	Device mount IP54-SDGSOB LED
Order number:	18610276600
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI + emergency lighting 3 hours (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	39
Ballast lumen factor BLF (emergency lighting mode):	10.4
Luminaire luminous flux (lm):	6000
lm/W:	149
Energy efficiency class:	A++
Certifications:	IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2.6
Dimensions LxWxH/DxH (mm):	1531 x 55 x 37
mounting method:	Mounting rail system mounting
EAN-number:	4020863325863
Commodity code:	94051098

SDGSOB LED 6000lm 840 • vw • EM pack 3h DALI • 18610276600



Lighting technology
Individual.Lens.Optic-direct wide distribution
SDGSOB LED 6000 lm 840



ηLB	100 %
lm/W	149
Φ ↓/↑	100 % / 0 %
UGR q/l	20.6 / 20.6



Quick-fit mounting system Device mount IP 54; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated pressure locks. Lighttechnical element with transparent seal, end faces made of plastic, all-round closed seal to mounting rail. Housing colour traffic white RAL 9016; Direct, open light distribution, individual. lens. optic made of polycarbonate. With 3 hours emergency lighting battery and integrated status indicator; 3 hours emergency lighting operation. Heat-resistant cables including permanently fixed, 6-pole rapid installation plug connector with tool-less phase pre-selection and locating finger; one wire of the through-wiring can be used as un-switched charging phase using an additional pole on the plug connector;

Dimensions LxWxH/DxH (mm): 1531 x 55 x 37
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 6000
lm/W: 149
Operating device: Electronic driver DALI + emergency lighting 3 hours (1 pcs.)
System performance (W): 39
Ballast lumen factor BLF (emergency lighting mode): 10.4
Energy efficiency class: A++
Certifications: IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGSOB LED 6000 840 NL-B3 DALI vw
Article number: 18610276600
Product deep link: http://www.regiolux.de/de/article/18610276600
5 year guarantee after registration on website.