


Category (ETIM):	Device mount IP 54/FF
Type:	Device mount IP54-SDGRS T5
Order number:	18802967700
Configuration:	Suitable for equipment fitting: T5 2x35/49W G5
Operating device:	Electronic ballast, multi emergency lighting 3 hours (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	104
Energy efficiency class:	A+
Energy efficiency class CELMA EEI:	A2
Certifications:	IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	6.6
Dimensions LxWxH/DxH (mm):	1533 x 194 x 105
mounting method:	Mounting rail system mounting
EAN-number:	4020863249688
Commodity code:	94051098

SDGRS T5 2x35/49W G5 • vw • ECG EM pack B3 • 18802967700



Lighting technology
Reflector device mount with highly specular mirror reflector insert and transparent cover pane-direct distribution
SDGRS 2x T5 49 W



Quick-fit mounting system Device mount IP 54/FF; Device mount insert made of galvanised profiled sheet steel; surface coated with polyester resin enamel coating; with two screw-on twist locks for quick and secure insertion into the mounting rail; for ensuring the protection rating with surrounding closed seal towards the mounting rail. In one unit with the sheet steel reflector with a clear, stable acrylic glass cover pane in aluminium frame profile with integrated PU foam coating, can be folded down on both sides and self-engaging. Housing colour traffic white RAL 9016; Direct wide light distribution using reflector with inner mirror reflectors made of high specular anodised aluminium and transparent cover pane. With 3 hours emergency light battery. Inverter; batteries and LED as functional check; three hours of emergency lighting with one lamp at reduced lamp luminous flux. Heat-resistant cables including permanently fixed 4-pole quick-mount plug connector with tool-free phase preselection and locating finger; one wire of the through-wiring can be used as unswitched charge phase using an additional pole on the plug connector;

Dimensions LxWxH/DxH (mm): 1533 x 194 x 105
Configuration: Suitable for equipment fitting: T5 2x35/49W G5
Operating device: Electronic ballast, multi emergency lighting 3 hours (1 pcs.)
System performance (W): 104
Energy efficiency class: A+
Energy efficiency class CELMA EEI: A2
Certifications: IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGRS T5 2x35/49 EVG NL-B3 vw
Article number: 18802967700
Product deep link: <http://www.regiolux.de/de/article/18802967700>