Datasheet


REGIOLUX

Category (ETIM):	Variable device mount
Type:	Device mount IP20-SDGVL LED
Order number:	18214574150
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver emergency light 3 hours (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	48
Ballast lumen factor BLF (emergency lighting mode):	9.6
Luminaire luminous flux (lm):	7000
lm/W:	145
Certifications:	IP 20, protection class I, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2.8
Dimensions LxWxH/DxH (mm):	1531 x 55 x 43
mounting method:	Mounting rail system mounting
EAN-number:	4020863336272
Commodity code:	94051098


SDGVL LED 7000lm 840 • vw • EM pack 3h • 18214574150



Lighting technology
open distribution-general diffuse
SDGVL LED 7000 lm 840



ηLB	100 %
lm/W	145
Φ ↓/↑	100 % / 0 %
UGR q/l	26.6 / 27.6



Quick-fit mounting system Variable device mount; Device mount with two lateral lever locks, made of galvanised, profiled sheet steel; surface coated with polyester resin enamel; LED unit made of natural anodised extruded aluminium profile, in housing length for optically seamless light run, end faces made of plastic; can be positioned variably in light run. Suitable for the mounting of LED light directing components. Housing colour traffic white RAL 9016; Light distribution direct as open distribution, matt LED diffuser cover made of polycarbonate. For optically seamless light run design. With 3 hours emergency lighting battery and integrated status indicator; 3 hours emergency lighting operation. Heat-resistant cables including permanently fixed, connection cable 1 m and 4-pole quick-mount plug including tool-less phase pre-selection and locating finger; one wire from the through-wiring can be used as unswitched load via an additional pole at the plug; Can be combined with the self-supporting specular reflectors SDFAL LED, SDFBL LED and SDFTL LED.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 43
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 7000
lm/W: 145
Operating device: Electronic driver emergency light 3 hours (1 pcs.)
System performance (W): 48
Ballast lumen factor BLF (emergency lighting mode): 9.6
Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH
Type: SDGVL LED 7000 840 NL-B3 vw
Article number: 18214574150
Product deep link: http://www.regiolux.de/de/article/18214574150
5 year guarantee after registration on website.