

Product name

SM-S1-PLUS-1400S-NA

Item number

9300172

Manufacturer

SOLAMAGIC



Product description

SOLAMAGIC S1+ infrared heater, switch, 1.4kW, anthr, IP44

The new premium infrared heater SOLAMAGIC S1+ is impressive not only with its improved, glare-free Solastar-HP heating tube, but also with its simple and quick mounting system and the integrated switch-on current limitation (for 2000 W devices). The casing is made of high-quality aluminium and is impressive with its elegant design. The newly developed Solastar-HP heating tube also combines a more pleasant light colour with perfect thermal behavior with minimal residual light and an average service life of 5,000 h. Especially in outdoor areas, infrared radiant heaters allow very flexible applications and create constant, pleasant heat zones on balconies, terraces or even in outdoor catering areas. Due to a short wavelength, infrared heat radiation penetrates air particularly efficiently, is not exposed to wind drifts and guarantees high operating cost savings compared to gas radiators. Colours: white, titanium, nano-anthracite, special colours on request, practical mounting accessories, high efficiency, no heating phase, can be dimmed via optional wireless or Bluetooth dimming module, power: 1400/2000 W, with on/off switch, protection rating: IP 44, protection rating: I, dimensions: 520x200x92 mm, certification mark: TÜV Nord, CE marking, weight: 3.0/3.2 kg, connection cable 50 cm with Schuko plug and Hirschmann coupling (loose enclosed), voltage: 230 V.

Technical Details

Model	Ceiling-/wall emitter	Voltage	230 230 Volt
Mounting method	Surface mounting	Number of heating levels	1
Power step OFF	✓	Min. heating power	1400 Watt
Mounting over cradle	✗	Max. heating power	1400 Watt
Degree of protection (IP)	IP44	Min. mounting height	1.8 Metre
Colour	Grey	Max. mounting height	2.2 Metre
Compatible with Apple HomeKit	✗	Height	92 Millimetre
Compatible with Google Assistant	✗	Width	520 Millimetre
Compatible with Amazon Alexa	✗	Depth	200 Millimetre
IFTTT support available	✗	RAL-number	0