

KombiSIGN 50 / Accessories

Contact box for cable exit at side



Part No.: 975.840.01

MECHANICAL DATA

Height	29 mm
Diameter	70 mm
Materials	PA-GF
Housing colour	Black
Protection category	IP54
Cable entry	Screwed cable gland
Cable entry minimum	d = 5 mm
Cable entry maximum	d = 10 mm
Weight with packaging	71 g
Product weight	71 g

APPROVAL DATA

Conforms with CE	No
Conforms with RoHS directive	Fulfills substance restriction
WEEE	No
Conforms with ATEX-directive	No
Conforms with CCC	No
Conforms with UL	No
Conforms with FCC	No
Conforms with IC	No
EAC certificate available	No
Conforms with UKCA (Importer)	No
Conforms with AS-I	No
ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Contact box for cable exit at side

Technical drawing of a 1/2 inch NPT female adapter. The drawing includes a side view and a top view.

Side View Dimensions:

- Thread: M16x1,5
- Flange Thickness: 1,5
- Flange Diameter: $\varnothing 70$
- Flange Height: 28,5

Top View Dimensions:

- Overall Diameter: $\varnothing 43$
- Flange Diameter: 56
- Flange Thickness: 15°
- Mounting Hole Diameter: $\varnothing 3,5$
- Mounting Hole Diameter: $\varnothing 4,4$
- Mounting Hole Diameter: 38
- Mounting Hole Diameter: 38

975.840.01

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.