PRODUCTINFORMATIEBLAD
DALI HIGHBAY ADAPTER

DALI HIGHBAY ADAPTER | Besturingseenheden voor lichtmanagementsystemen

Toepassingsgebieden

- Industry
- Production halls
- Sports halls
- Logistic centers
- Areas with high ceilings
- Connection of light and presence sensors in DALI systems
- Suitable for indoor installations
- Production and assembly facilities
- Open-plan offices, corridors and storage rooms
- Corridors
- Strip lighting in factory halls

Productvoordelen

- Sensor integration in DALI
- Embedding of HIGH BAY and VISION motion sensors into DALI
- Extended terminal section enables mains looping
- Daylight-dependent control with automatic shutdown in aquate daylight
- DALI based light management system integrable into building management systems
- Flexible addressing via DALI

Productkenmerken

- DALI adapter for HIGH BAY and VISION sensor
- Direct connection to DALI
- Connection via screwless push wire terminals
- Light sensor working range: 20...800 lx (measured at sensor)
- Integrated light sensor
- Suitable for through wiring
- Suitable for daylight-dependent control
- Light regulation for mounting heights of up to 13 m

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

- Power supply for coupler from DALI
- Integration into BMS systems

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

TECHNISCHE GEGEVENS

ELEKTRISCHE GEGEVENS

Nominale vermogen	0,10 W
Nominale spanning	20 V
Netfrequentie	0 Hz

AFMETINGEN & GEWICHT



Lengte	139.00 mm
Breedte	118.00 mm
Breedte (incl. ronde armaturen)	118.00 mm
Hoogte	37.00 mm
Hoogte (incl. cylin. armaturen)	37.00 mm
Product gewicht	74,00 g

KLEUREN & MATERIALEN

Kleur van het product	Wit

TEMPERATUREN & BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	0...+50 °C

MOGELIJKHEDEN

Dimmable	Nee
Dimmer interface	DALI
Maximale inbouwhoogte	13 m
Type montage	Montage/plafond
Bereik van de lichtsensor	20...800 lx [1]

[1] Bij benadering, gemeten bij de sensor

CERTIFICATEN & NORMEN

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Keurmerken	CE
Veiligheidsklasse	II
Type bescherming	IP20

EQUIPMENT / ACCESSORIES

- Blind cover included
- Suitable for the DALI Professional light control system

DOWNLOADS

	DOWNLOADS
PDF	User instruction
PDF	Declarations of conformity
ZIP	CAD data 3-dim
PDF	Advertisements

LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4008321774132	Vouwdoos 1	356 mm x 22 mm x 29 mm	266.00 g	0.23 dm^3
4008321774149	Verzenddoos 20	270 mm x 225 mm x 285 mm	2668.00 g	17.31 dm^3

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendeenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.