PRODUCT DATASHEET
SubstiTUBE T8 HF Pro 14 W/3000 K 1200 mm

SubstiTUBE® PRO HF | LED tubes for electronic high frequency control gears (ECG), shatterproof



Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Supermarkets and department stores
- Industry
- Offices, public buildings

Product benefits

- Quick, simple and safe replacement without rewiring
- Shatter protection thanks to special PET coating
- Also suitable for operation at low temperatures
- High luminous flux for sophisticated lighting tasks
- No bending thanks to glass technology

Product features

- T8 LED tube made of glass with G13 base
- Low flicker according to EU 2019/2020
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime: up to 60,000 h
- Compatible with many common electronic control gears (see also compatibility list)





© 2022, LEDVANCE GmbH. All rights reserved.


TECHNICAL DATA

Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	40…70 V
Claimed equiv. conventional lamp power	36 W
Nominal current	80 mA
Type of current	AC
Inrush current	20 A
Operating frequency	20…75 kHz
Mains frequency	20…75 kHz
Total harmonic distortion	< 20 %
Power factor λ	> 0.90

Photometrical data

Luminous flux	1900 lm
Luminous efficacy	135 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	83
Light color	830
Standard deviation of color matching	≤5 sdcm




Light technical data

Beam angle	190 °
Warm-up time (60 %)	‹ 2.00 s
Starting time	< 0.5 s

© 2022, LEDVANCE GmbH. All rights reserved.

Rated beam angle (half peak value)	190.00 °

Dimensions & Weight



Overall length	1212.50 mm
Diameter	27.80 mm
Tube diameter	25,5 mm
Maximum diameter	28 mm
Product weight	200.00 g

Temperatures & operating conditions

Ambient temperature range	-20…+45 °C
Maximum temperature at tc test point	68 °C

Lifespan

Nominal lamp life time	60000 h
Number of switching cycles	200000
Lumen maintenance at end of serv	0.70
Rated lamp survival factor at 6,000	≥ 0.90

Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	E [1)]
Energy consumption	16.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0

© 2022, LEDVANCE GmbH. All rights reserved.

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order reference	LEDTUBE T8 HF P

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C

Energy labellling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	1212.50 mm
Height	27.80 mm
Width	27.80 mm
Chromaticity coordinate x	0.433
Chromaticity coordinate y	0.403
Beam angle	SPHERE_360
Survival factor	0.90
Displacement factor	0.90
LED light source replaces a fluorescent light source	not applicable
EPREL ID	519420,519420
Model number	AC33857,AC33857

Safety advice

- Not suitable for operation with low-loss and conventional control gears and main voltage.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc max temperature on the product prior to installation.

© 2022, LEDVANCE GmbH. All rights reserved.

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	Installation guide SubstiTUBE® T8 T5
PDF	Installation guide Installationsanleitung SubstiTUBE T8 T5
	IES file (IES) ST8PRO 1.2M 14W 830 40-70V HF OSRAM
	LDT file (Eulumdat) ST8PRO 1.2M 14W 830 40-70V HF OSRAM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075545137	Sleeve 1	1,220 mm x 31 mm x 31 mm	223.00 g	1.17 dm^3
4058075545144	Shipping box 10	1,272 mm x 210 mm x 115 mm	2863.00 g	30.72 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2022, LEDVANCE GmbH. All rights reserved.