PRODUCT DATASHEET
DULUX T/E PLUS 13 W/827

OSRAM DULUX® T/E PLUS | CFLni, 3 tubes, with 4-pin base for ECG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industrial lighting

Product benefits

- Improved maintenance

Product features

- Good color rendering index
- Dimmable (3...100 %)
- Short and compact pin-base lamp with triple-turn tubes
- Single-ended four-pin plug-in GX24q base with shortened base casing





© 2024, LEDVANCE GmbH. All rights reserved.


TECHNICAL DATA

Electrical data

Nominal wattage	13 W
Construction wattage	14.20 W
Nominal voltage	91 V
Nominal current	0.18 A


Photometrical data

Luminous flux	850 lm
Luminous efficacy	60 lm/W
Light color (designation)	LUMILUX INTERNA
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.84
Rated LLMF at 6,000 h	0.83
Rated LLMF at 8,000 h	0.81
Rated LLMF at 12,000 h	0.79
Rated LLMF at 16,000 h	0.78
Rated LLMF at 20,000 h	0.77



Dimensions & Weight

© 2024, LEDVANCE GmbH. All rights reserved.



Overall length	106.50 mm
Length with base excl. base pins/connection	90,00 mm
Diameter	12.00 mm
Tube diameter	12 mm
Product weight	52.3 g

Temperatures & operating conditions

Ambient temperature range	-5…+40 °C

Lifespan

Service life	13000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.81
Rated lamp survival factor at 20,000 h	0.50
Lifespan B50	20000 h

Additional product data

Base (standard designation)	GX24q-1
Mercury content	2.0 mg

Capabilities

Dimmable	Yes

Certificates & Standards

Energy efficiency class	G

© 2024, LEDVANCE GmbH. All rights reserved.

Energy consumption	14.00 kWh/1000h

Country-specific categorizations

ILCOS	FSMH-13/827-/P/-GX24q-1
Order reference	DULUX T/E 13W/8

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	CFLNI
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GX24q-1
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	106.50 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0,463
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546461
Model number	AC34236

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

© 2024, LEDVANCE GmbH. All rights reserved.

	Documents and certificates
PDF	Declarations Of Conformity CE
PDF	Certificates

	Photometric and lighting design files
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300447001	Folding box 1	49 mm x 46 mm x 121 mm	61.00 g	0.27 dm^3
4050300447018	Shipping box 10	240 mm x 106 mm x 134 mm	714.00 g	3.41 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, LEDVANCE GmbH. All rights reserved.