
PRODUCT DATASHEET
LFP3000 -G3-827-03

LINEARlight FLEX® Protect POWER 3000 | LED modules for professional and industrial applications



Areas of application

- Facade accent lighting
- Ceiling integration
- Wall integration
- Cove lighting
- Machine lighting
- Path lighting
- Suitable for outdoor use

Product benefits

- Color uniformity better than 2 SDCM on the entire LED strip and between strips
- High luminous flux
- Great design freedom thanks to flexibility and cuttability of module
- High-performance silicone for extremely long life and flexibility
- Simple connection thanks to premounted connectors
- Extraordinary design and high quality materials
- Toolless connection only if using the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- Outdoor use possible: UV and salt mist resistant (UV acc. to ISO 4892-2 - Method A, salt mist acc. to IEC 60068-2-52 severity 1)

Product features

- Flexible and cuttable LED strip



© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

- Luminous flux: up to 3,000 lm/m
- Type of protection: IP67
- Dimmable with PWM technology

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	86.70 W
Construction wattage	86.70 W
Nominal wattage per meter	28.9 W
Nominal voltage	24 V
Input voltage range	23…24 V
Reverse Voltage	25 V
Type of current	DC
Nominal current	3610 mA

Photometrical data

Total useful luminous flux [PICOS]	9000 lm
Luminous efficacy	104 lm/W
Luminous flux	9000 lm
Luminous flux per meter	3000 lm
Color temperature	2700 K
Color rendering index Ra	> 80
Light color LED	White
Light color (designation)	2700 K
Standard deviation of color matching	≤4 sdcm
Lumen main.fact.at end of nom.life time	0.70

Light technical data


Beam angle	120 °
Rated beam angle (half peak value)	120.00 °
Starting time	< 0.5 s
Warm-up time (60 %) [AGGR]	0.00 s

LED MODULE INFORMATION

Number of LEDs per meter	70
Number of LEDs per module	210
Number of LEDs per smallest unit	7

Dimensions & Weight

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.



Length	3000 mm
Length – smallest unit	100 mm
Width	11.00 mm
Height	4.50 mm
Cable cross-section, input side	0.34 mm²
Conductor cross section	0.34 mm²
LED pitch	14.3 mm
Product weight	195.00 g

Colors & materials

Cover material	Silicone

Temperatures & operating conditions

Ambient temperature range	-20…+50 °C
Maximum temperature at tc test point	70 °C
Temperature range in operation	-20…70 °C [1)]
Performance temp. acc. to IEC 62717	60 °C [2)]

1) Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

2) Tp rated. Tp point coincides with Tc point - marked on device

Lifespan

Nominal lamp life time	60000 h
Number of switching cycles	›15000

Additional product data

Product remark	Modules perfectly matched to OSRAM OPTOTRONIC® LED drivers (see relevant table) / For current photometric data and important safety, installation and application information, see www.osram.com/led-systems. / All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

Capabilities

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

Dimmable	Yes
Dimming interface	PWM
Type of installation	Surface mounting
Lowest bending radius	50 mm
Self-adhesive	Yes

Certificates & Standards

Standards	CE; ENEC 10 VDE / EAC / UL Recognized component according UL 8750
Type of protection	IP67
Energy consumption	95.00 kWh/1000h
Energy efficiency class	A+

LOGISTICAL DATA

Temperature range at storage	-40…+85 °C

EQUIPMENT / ACCESSORIES

- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V electronic control gears

ADDITIONAL PRODUCT INFORMATION

- Some LED modules are equipped with a self-adhesive tape for attaching the LED module to suitable materials, such as aluminum profiles, which must be clean and free of oil or silicone coatings, as well as other dirt/dust particles. The adhesive tape is intended for single use and if removed may damage the material to which it is stuck and the LED module itself, which must then be scrapped. Use the adhesive tape when the installation material temperature is in the 18 °C…35 °C range. Complete adhesion takes up to 72 h.
- LED modules are designed for static installations in accordance with IPC 6013C – Use A. Take material vibrations, repetitive torsion, and elongation/compression into account.
- If the operating environment covers a broad temperature range (e.g. outdoor applications) and the operating length is longer than 2 m, the use of adequate mounting surfaces is required. The use of an additional thicker adhesive tape between LED module and mounting surface is also recommended in order to absorb the stress of any mismatch in expansion. Assure enough space for module expansion with increasing temperature.
- The manufacturer is not responsible for damage due to chemical corrosion. The user must provide suitable protection against corrosive agents such as moisture and condensation and any other harmful elements/compounds. Make certain to avoid corrosive atmospheres. According to the current state of LED technology, hydrogen sulfide (H2S) causes accelerated corrosion which leads to shortened lifetime or premature failure. Sources of H2S may be rubber, foam rubber, soft-foam tapes, rubber-based sealing, natural sources (e.g. sulfur springs), etc. To avoid H2S from sulfur-vulcanized rubber use silicon-based materials or peroxide-crosslinked rubber instead. Follow the recommendations in the material datasheet of the rubber supplier.
- IP00 LED modules, as manufactured, have no conformal coating and therefore offer no inherent protection against corrosion. Conformal coating treatment is possible, however materials must be selected properly in order to avoid product damage or impaired performance; the user must also completely seal the cut parts (ends/edges).
- For applications involving exposure to humidity and dust the module must be protected by a fixture or housing with a suitable IP protection class.
- Consult OSRAM Technical Service for further advice.
- Only a qualified electrician may install the module.
- Handle with care and ensure that there is no mechanical product damage, including damage to invisible internal electronics parts.
- Exceeding maximum operating and storage temperature ratings can reduces the expected lifetime or even destroy the LED module. The

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

temperature of the LED module must be measured at the Tc-point in accordance with EN 60598-1 under steady-state conditions, considering the worst case; drive all channels at 100 % power. Refer to the product drawing for the exact location of the Tc-point.
- Exceeding the maximum ratings for the operating voltage causes hazardous overload and will likely destroy the LED module.
- Installation of LED modules and connection to the power supply must comply with all applicable electrical and safety standards.
- Observe correct polarity and wiring diagrams! Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Never exceed the maximum operable length, including daisy-chaining connections.
- Always ensure electrical isolation between the LED module and the mounting surface, especially in the vicinity of connections or cut ends.
- IP00 LED modules are ESD-sensitive; take adequate precautions during installation and operation of the products.
- Use only SELV LED drivers in accordance with applicable lighting standards and LED module ratings. In order to safely operate OSRAM LED modules it is necessary to supply them with an electronically stabilized power supply providing protection against short circuits, overload and overheating. To simplify the approval process of the luminaire/installation, the electronic power supplies control gear for LED modules must bear the CE and ENEC marking. In Europe the Declarations of Conformity must include at least the following standards: EN 61347-2-13, EN 55015, EN 61547 and EN 61000-3-2. ENEC certification will be based on EN 61347-2-13 and EN 62384. OSRAM OPTOTRONIC LED drivers comply with all relevant standards and guarantee safe operation; see the relevant brochure for more detailed information about OSRAM OPTOTRONIC.
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction LINEARlight FLEX Protect POWER
PDF	PRODUCT DATASHEET LINEARlight FLEX Protect Power Specification Sheet
PDF	Certificates VDE ENEC+ Certificate LFP3000-G3
PDF	Certificates UL Certificate
PDF	Certificates EAC Certificate
PDF	Certificates ENEC10_VDE Certificate
PDF	Declarations of conformity Declaration of conformity
PDF	Declarations of conformity Manufacturer declaration
	IES file (IES) IES LFP3000-G3-827
	LDT file (Eulumdat) Eulumdat LFP3000-G3-827
PDF	Advertisements Light is freedom of design (EN)

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.

	DOWNLOAD DATA
PDF	Advertisements 729674_Light is freedom of design (EN)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899481312	Folding box 1	353 mm x 349 mm x 32 mm	347.00 g	3.94 dm^3
4052899481329	Shipping box 8	365 mm x 286 mm x 366 mm	5215.00 g	38.21 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2022, products of OSRAM GmbH, distributed by LEDVANCE GmbH. All rights reserved.