

# 201710
# TKHM-W-10/LP
# Connection cable

- LEDs for service voltage and switching status
- Drag chain compatible
- Sturdy metal union nut
- Durable PU coating
- Flexible lead design
- Good stripping properties
- High protection type
- Gold-plated plug-in contacts






1) Mounting free space from upper edge of plug connector
2) LED (2x) only with TKHM-W- ... / LP
BK: black
BN: brown
BU: blue

| Function |
|---|

| Technical data (typ.) | |
|---|---|
| Service voltage | < 30 V DC |
| Length | 10,000 mm |
| Diameter | Ø 4.5 mm (Diameter) |
| Thread | M8 x 1 |
| Material of cable | Polyurethane |
| Drag chain properties | 70 mm (Min. bending radius) |
| Protection class | III, operation on protective low voltage |
| Design | Angled / open cable end |
| Characteristics | Metal nut |
| Drag chain compatible | Yes |
| LED Anzeige | Yes |
| Ambient temperature during operation | -5 … +80 °C (Movable, Fixed) |
| Protection type | IP 67 |
| Connection | Socket, M8, 3-pin, A-coded |
| Cross-section | 0.25 $mm^2$ (3 x) |

| More information / accessories | https://www.di-soric.com/201710 |
|---|---|


© di-soric . Right to change reserved