



13P-320532: T-with female branch 32x3/4"x32



Commercial information

The body of the fitting is made from CW617N brass. These fittings offer great advantages with regard to corrosion and they are also also better for the environment.

- The fitting has a buffer ring that prevents direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- This excludes the possibility of electrolysis occurring.
- The fitting is equipped with O-rings made from EPDM and RVS pressure sleeves with 3 inspection windows.
- In order to prevent assembly errors, the dimensions and type of press profile which can be pressed are shown on the RVS sleeves

Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

Solutions

Building installations, Industry, Utility, Shipbuilding

Technical characteristics

Material connection 1	Brass	Angle	90 Degrees
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	32 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 3	32 Millimetre
Material connection 2	Brass	Length of connection 1	45 Millimetre
Surface protection connection 2	Untreated	Working length connection 1	0 Millimetre
Surface treatment connection 2	Untreated	Length of connection 2	17.5 Millimetre
Material connection 3	Brass	Working length connection 2	0 Millimetre
Surface treatment connection 3	Untreated	Length of connection 3	45 Millimetre
Model	T-piece	Working length connection 3	0 Millimetre
Swept entry type (with inner radius)	✗	Wrench width	0 Millimetre
Reducing	✗	Max. operating pressure at 20 °C	10 Bar
System specific	✓	Wrench width union nut	0 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code connection 1	BE	Standard Dimension Ratio (SDR)	0
Nominal diameter connection 2	3/4 inch (20)		
Connection 2	Internal thread cylindrical BSPP-G (ISO 228-1)		
Connection 3	Press sleeve		
Contour code connection 3	BE		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
High tensile strength	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
With drain valve	✗		
With de-aerator	✗		
With thermal insulation	✗		
With buffer stud	✗		
Capped	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		

Related products

Product code	GTIN	Description
BE32MINI3	05414764014244	Henco Jaw for press machine M-BMINI3 BE/TH-Profile 32mm

Image

