

HNAFL-DN50: Flange connection HNA Ø75 x DN50



Commercial information

Certificates

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Stainless steel	Bend radius	0 Millimetre
Material quality connection 1	Stainless steel 304 (1.4301)	Length	165 Millimetre
Surface protection connection 1	Untreated	Medium temperature (continuous)	-10 70 Degrees celsius
Surface treatment connection 1	Untreated	Max. operating pressure at 20 °C	10 Bar
Material connection 2	Stainless steel		
Material quality connection 2	Stainless steel 304 (1.4301)		
Shape	Straight		
Reducing	✓		
Eccentric	✗		
System specific	✓		
Nominal diameter connection 2	3/4 inch (20)		
Self-sealing	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✗		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
VdS quality mark	✗		
KIWA certified	✗		
Gastec QA mark	✗		

Related products

Product code	GTIN	Description
HNA	05414764430884	Henco Bracket set 75mm

Image

