VISION SET 16: Vision set Ø 16 (sleeve + 2 O-rings)



Commercial information

Henco revision set contains 2 O-rings and sleeve

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	0	Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Outer pipe diameter connection 1	16	Millimetre
Surface protection connection 1	Untreated	Length	37	Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0	Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Medium temperature (continuous)	-10|70	Degrees celsius
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Max. operating pressure at 20 °C	10	Bar
Surface protection connection 2	Untreated	Standard Dimension Ratio (SDR)	0	
Surface treatment connection 2	Untreated			
Reducing	✖			
Eccentric	✖			
System specific	✔			
Connection 1	Insert (push-fitting)			
Main colour fitting	White			
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)			
With buffer stud	✖			
Self-sealing	✖			
With thermal insulation	✖			
Ring stiffness class	Other			
With sealing rings/gaskets	✔			
Capped	✖			
With connection indicator	✖			
With drain valve	✖			
With de-aerator	✖			
FM quality mark	✖			
LPCB quality mark	✖			
ULC quality mark	✖			
UL quality mark	✖			
VdS quality mark	✖			
With approval for TÜV	✖			
DVGW quality mark for gas	✖			
DVGW quality mark for water	✔			
KIWA certified	✔			
Gastec QA mark	✖			
KOMO certified	✔			
Type approval according to BBR/EKS	✖			

Related products