12PK-507550: Verloop T-stuk 50x75x50



Commerciële informatie

The Henco Super Size range refers to the Henco multilayer pipe and the Henco fittings in diameters 75 - 90 - 110 mm,
with reducing couplings for diameters 32 - 40 - 50 - 63 mm. The fittings assure a complete multilayer piping system with multiple variations for distribution and riser systems. The numerous combinations and the revolutionary connection technique make this system extremely flexible. The Henco Super Size fittings are made of the Polyvinylidene Fluoride (PVDF), a high quality synthetic material. The PVDF
offers the user a unique combination of properties:
- corrosion resistant
- excellent mechanical strength and hardness
- resistant to extreme temperatures: from -40°C to +150°C
- approved for contact with water and food
- a maximum working pressure up till 10 bar and amaximum working temperature up till 95°C

All these favourable properties make this multilayer system suitable for numerous applications such as drinking water installations, heating installations and installations in the chemical and food industry. The Henco Super Size fittings are just like all other Henco fittings designed with a leak before press detection.

Insteekdiepte 1 (es1)	51,0 Millimeter

Certificaten

KIWA, KOMO, DVGW Wasser, ATG, ETA, SINTEF, RISE, STF, QB (CSTBat), AFNOR, ACS, WRAS, DNV-GL

Toepassingen

Drinkwater, Verwarming, Perslucht, Koeling, Demi water, Sanitair

Oplossingen

Gebouwinstallaties, Industrie, Infra

Technische kenmerken

Materiaal aansluiting 1	Polyvinylidenefluoride (PVDF)	Hoek	90 Hoekgraden
Oppervlaktebescherming aansluiting 1	Onbehandeld	Uitwendige buisdiameter aansluiting 1	50 Millimeter
Oppervlaktebehandeling aansluiting 1	Onbehandeld	Wanddikte aansluiting 1	0,9 Millimeter
Materiaal aansluiting 2	Polyvinylidenefluoride (PVDF)	Uitwendige buisdiameter aansluiting 2	75 Millimeter
Oppervlaktebescherming aansluiting 2	Onbehandeld	Uitwendige buisdiameter aansluiting 3	50 Millimeter
Oppervlaktebehandeling aansluiting 2	Onbehandeld	Wanddikte aansluiting 3	0,9 Millimeter
Materiaal aansluiting 3	Polyvinylidenefluoride (PVDF)	Sleutelwijdte	0 Millimeter
Model	T-stuk	Max. werkdruk bij 20°C	10 bar
Stromende uitvoering (met binnenradius)	✖	Sleutelwijdte wartel	0 Millimeter
Verlopend	✔	Mediumtemperatuur (continu)	-10|70 Graden Celsius
Systeemgebonden	✔	Standard Dimension Ratio (SDR)	0

Aansluiting 1	Persmof
Aansluiting 2	Persmof
Aansluiting 3	Persmof
Materiaal afdichting	Ethyleen-Propyleen-Dieen-Monomeer (EPDM)
Hoofdkleur fitting	Zwart
Hoge treksterkte	✖
Ringstijfheidsklasse	Overig
Met pakkingen	✔
Met aftapper	✖
Met ontluchter	✖
Met thermische isolatie	✖
Met stootnok/-rand	✔
Afgedopt	✖
FM keur	✖
LPCB keur	✖
ULC keur	✖
UL-keur	✖
DIN-CERTCO certificaat	✖
VdS keur	✖
Met TUV goedkeuring	✖
DVGW-keur voor gas	✖
DVGW-keur voor water	✔
KIWA-keur	✔
Gastec QA	✖
KOMO-keur	✔
Type goedkeuring volgens BBR / EKS	✖

Gerelateerde producten

Productcode	GTIN	Omschrijving	Afbeelding
HNTOOLSET	05414764409569	Henco Toolset voor Super Size	
BE50	05414764409569	Henco Persbekken (universeel) BE-Profiel 50x4	