



CU-6ZONE-24V: Base Module 6 Zones, 24V Transformator Incl.



Commercial information

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Networkable via radiografic (standard)	✗	Supply voltage	24 Volt
Networkable via radio (optional)	✗	Output voltage	24 Volt
Connection for external antenna	✗	Number of channels/zone	6
Smart control	✓	Max. power per channel	50 Voltampere
Suitable for heating	✓	Reception frequency	0 Megahertz
Suitable for cooling	✓	Max. contact voltage	24 Volt
With time switch clock	✓	Max. contact load	2 Ampere
With extra contact	✓	Width	90 Millimetre
Contact type	Normally open contact (NO)	Height	52 Millimetre
Degree of protection (IP)	IP20	Depth	325 Millimetre

Related products

Product code	GTIN	Description	Image
BE26	05414764309425	Henco Jaws (universal) BE/TH-Profile 26x3	
CU-ACT-24V-PLUG	05414764309425	Henco Act For Plugcable, 24V	
CU-REGC-24V	05414764309425	Henco Lcd Control Thermostat 24V	
CU-REGK-24V	05414764309425	Henco Lcd Komfort Thermostat 24V	
CU-REGB-24V	05414764309425	Henco Analog Thermostat 24V	
CU-DINRAIL	05414764309425	Henco Din Rail	