VVPK-20: Straight entry piece - Press Ø20



Commercial information

Straight entry piece - Press

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, EMI, TSU

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	0 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Outer pipe diameter connection 1	20 Millimetre
Surface protection connection 1	Untreated	Wall thickness, connection 1	0.7 Millimetre
Surface treatment connection 1	Untreated	Length	66.6 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Wrench width	0 Millimetre
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Wrench width union nut	0 Millimetre
Surface protection connection 2	Untreated	Medium temperature (continuous)	-10|70 Degrees celsius
Surface treatment connection 2	Untreated	Max. operating pressure at 20 °C	10 Bar
Shape	Straight	Standard Dimension Ratio (SDR)	0

Reducing	✖
Eccentric	✖
System specific	✔
Connection 1	Press sleeve
Main colour fitting	White
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)
With buffer stud	✔
High tensile strength	✖
With thermal insulation	✖
Ring stiffness class	Other
With sealing rings/gaskets	✔
Capped	✖
With drain valve	✖
With de-aerator	✖
FM quality mark	✖
LPCB quality mark	✖
ULC quality mark	✖
UL quality mark	✖
DIN-CERTCO certificate	✖
VdS quality mark	✖
With approval for TÜV	✖
DVGW quality mark for gas	✖
DVGW quality mark for water	✔
KIWA certified	✔
Gastec QA mark	✖
KOMO certified	✔
Type approval according to BBR/EKS	✖

Related products