

## 17P-2005: Straight male adapter 20x3/4"



### Commercial information

The body of the fitting is made from CW617N brass. These fittings offer great advantages with regard to corrosion and they are also also better for the environment.

- The fitting has a buffer ring that prevents direct galvanic contact between the aluminium of the pipe and the brass of the fitting.
- This excludes the possibility of electrolysis occurring.
- The fitting is equipped with O-rings made from EPDM and RVS pressure sleeves with 3 inspection windows.
- In order to prevent assembly errors, the dimensions and type of press profile which can be pressed are shown on the RVS sleeves

### Certificates

ATG, DVGW Wasser, ETA, KIWA, ÖVGW Wasser, WRAS, KOMO, STF, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, QB (CSTBat), AFNOR, ACS, PZH, DNV-GL, EMI

### Applications

Potable water, Heating, Compressed air, Cooling, Sanitary

### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                                    |                                                       |                                  |                        |
|------------------------------------|-------------------------------------------------------|----------------------------------|------------------------|
| Material connection 1              | Brass                                                 | Bend radius                      | 0 Millimetre           |
| Material quality connection 1      | CuZn40Pb2 (CW617N)                                    | Outer pipe diameter connection 1 | 20 Millimetre          |
| Surface protection connection 1    | Untreated                                             | Length                           | 55 Millimetre          |
| Surface treatment connection 1     | Untreated                                             | Length of connection 1           | 37 Millimetre          |
| Material connection 2              | Brass                                                 | Working length connection 1      | 37 Millimetre          |
| Material quality connection 2      | CuZn40Pb2 (CW617N)                                    | Length of connection 2           | 18 Millimetre          |
| Surface protection connection 2    | Untreated                                             | Working length connection 2      | 18 Millimetre          |
| Surface treatment connection 2     | Untreated                                             | Wrench width                     | 0 Millimetre           |
| Shape                              | Straight                                              | Wrench width union nut           | 0 Millimetre           |
| Reducing                           | ✗                                                     | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Eccentric                          | ✗                                                     | Max. operating pressure at 20 °C | 16 Bar                 |
| System specific                    | ✓                                                     | Standard Dimension Ratio (SDR)   | 0                      |
| Connection 1                       | Press sleeve                                          |                                  |                        |
| Contour code connection 1          | TH                                                    |                                  |                        |
| Nominal diameter connection 2      | 3/4 inch (20)                                         |                                  |                        |
| Connection 2                       | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |                                  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM)        |                                  |                        |
| With buffer stud                   | ✓                                                     |                                  |                        |
| High tensile strength              | ✗                                                     |                                  |                        |
| With thermal insulation            | ✗                                                     |                                  |                        |
| Ring stiffness class               | Other                                                 |                                  |                        |
| With sealing rings/gaskets         | ✓                                                     |                                  |                        |
| Capped                             | ✗                                                     |                                  |                        |
| With drain valve                   | ✗                                                     |                                  |                        |
| With de-aerator                    | ✗                                                     |                                  |                        |
| FM quality mark                    | ✗                                                     |                                  |                        |
| LPCB quality mark                  | ✗                                                     |                                  |                        |
| ULC quality mark                   | ✗                                                     |                                  |                        |
| UL quality mark                    | ✗                                                     |                                  |                        |
| DIN-CERTCO certificate             | ✗                                                     |                                  |                        |
| VdS quality mark                   | ✗                                                     |                                  |                        |
| With approval for TÜV              | ✗                                                     |                                  |                        |
| DVGW quality mark for gas          | ✗                                                     |                                  |                        |
| DVGW quality mark for water        | ✓                                                     |                                  |                        |
| KIWA certified                     | ✓                                                     |                                  |                        |
| Gastec QA mark                     | ✗                                                     |                                  |                        |
| KOMO certified                     | ✓                                                     |                                  |                        |
| Type approval according to BBR/EKS | ✗                                                     |                                  |                        |

## Related products

| Product code | GTIN           | Description                                             |
|--------------|----------------|---------------------------------------------------------|
| BE20MINI3    | 05414764019546 | Henco Jaw for press machine M-BMINI3 BE/TH-Profile 20mm |

Image

