



CU-ACT-24V-PLUG: Act For Plugcable, 24V



Commercial information

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Model	Wax-filled	Cable length	0 Metre
Connection to stop valve	M30 x 1.5	Operating time	210 Second
Supply voltage	230 V AC	Stroke length	4 Millimetre
Control signal	0 - 10 V	Ambient temperature	0 60 Degrees celsius
Function	Deactivated when closed NC	Nominal power	1 Voltampere
Automatic stroke recognition	✗	Max. electric power input	1 Voltampere
Protected against overvoltage	✓	Length	1000 Millimetre
Auxiliary contacts	✗	Width	60 Millimetre
With end contacts	✗	Height	55 Millimetre
First open	✓	Diameter	44 Millimetre
With position indicator	✓		
With valve adapter	✓		
Self-adjusting travel length	✗		
Colour	White		
Degree of protection (IP)	IP54		

Related products

Product code	GTIN	Description	Image
BE32	05414764309883	Henco Jaws (universal) BE-Profile 32x3	
UFH-ANC-05	05414764309883	Henco Valve 2x3/4 -M30x1,5-KV 2	
UFH-ANC-06	05414764309883	Henco Valve 2x1 -M30x1,5-KV 4,5	
CU-PLUGCABLE-2M	05414764309883	Henco Actuator Plugcable 2mtrs	
CU-PLUGCABLE-15M	05414764309883	Henco Actuator Plugcable 15mtrs	
CU-PLUGCABLE-5M	05414764309883	Henco Actuator Plugcable 5mtrs	