VDSK-26: Straight female adapter for manifold or manifold extension Ø26





Commercial information

Synthetic coupling for mounting on manifold (female)

Certificates

QB (CSTBat), ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	0 Millimetre
Material quality connection 1	Polyvinylidene fluoride (PVDF) (expired)	Outer pipe diameter connection 1	26 Millimetre
Surface protection connection 1	Untreated	Length	66 Millimetre
Surface treatment connection 1	Untreated	Wrench width union nut	0 Millimetre
Material connection 2	Polyvinylidene fluoride (PVDF)	Tightening moment	0|0 Newtonmetre
Material quality connection 2	Polyvinylidene fluoride (PVDF) (expired)	Medium temperature (continuous)	-10|70 Degrees celsius
Surface protection connection 2	Untreated	Max. operating pressure at 20 °C	10 Bar
Surface treatment connection 2	Untreated	Standard Dimension Ratio (SDR)	0

Shape	Straight
Reducing	✖
Eccentric	✖
System specific	✔
Connection 1	Insert (push-fitting)
Main colour fitting	White
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)
With buffer stud	✔
High tensile strength	✖
With thermal insulation	✖
Ring stiffness class	Other
With sealing rings/gaskets	✔
Capped	✖
With connection indicator	✖
With drain valve	✖
With de-aerator	✖
FM quality mark	✖
LPCB quality mark	✖
ULC quality mark	✖
UL quality mark	✖
DIN-CERTCO certificate	✖
VdS quality mark	✖
With approval for TÜV	✖
DVGW quality mark for gas	✖
DVGW quality mark for water	✔
KIWA certified	✔
Gastec QA mark	✖
KOMO certified	✔
Type approval according to BBR/EKS	✖

Related products