CU-ACT-24V: Act With Cable 1M, 24V



Commercial information

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Model	Wax-filled	Cable length	1 Metre
Connection to stop valve	M30 x 1.5	Operating time	210 Second
Supply voltage	24 V AC	Stroke length	4 Millimetre
Control signal	0 - 10 V	Ambient temperature	0|60 Degrees celsius
Function	Deactivated when closed NC	Nominal power	1 Voltampere
Automatic stroke recognition	✖	Max. electric power input	1 Voltampere
Protected against overvoltage	✔	Length	1000 Millimetre
Auxiliary contacts	✖	Width	45 Millimetre
With end contacts	✖	Height	60 Millimetre
First open	✔	Diameter	44 Millimetre
With position indicator	✔		
With valve adapter	✔		
Self-adjusting travel length	✖		
Colour	White		
Degree of protection (IP)	IP54		

Related products

Product code	GTIN	Description	Image
BE26	05414764309845	Henco Jaws (universal) BE/TH-Profile 26x3	
UFH-ANC-05	05414764309845	Henco Valve 2x3/4 -M30x1,5-KV 2	
UFH-ANC-06	05414764309845	Henco Valve 2x1 -M30x1,5-KV 4,5	