
# **UFH-0505SSTN11-PN6:** 11-groups steel collect. with pump, district heating nuon PN6



## Commercial information

- Stalen verdeler voor woningbouw waarbij de energieleverancier Nuon of Eneco is
- Deze verdeler is geschikt voor zowel hoofd- als bijverwarming bij diverse HR-ketels (volgens regelgeving GIW/ISSO 2007)
- Aanvoer en retour van de groepen liggen boven elkaar voor een goede en vlotte aansluiting
- Uitgangen worden euroconus 3/4” aangesloten

**Certificates**

**Applications**

Heating, Cooling, Underfloor Heating

**Solutions**

Underfloor heating, Building installations, Industry, Energy/district heating, Utility

## Technical characteristics

| | | | |
|---|---|---|---|
| Connection type primary side | 2-pipe | Outer pipe diameter primary connection | 32 Millimetre |
| Suitable for cooling | ✔ | Medium temperature (continuous) | 10\|60 Degrees celsius |
| Material | Steel | Max. operating pressure | 6 Bar |
| Position primary connection | Atop | Max. number of expansion groups | 0 |
| Primary connection | Internal thread cylindrical BSPP-G (ISO 228-1) | Supply voltage | 230 Volt |
| Nominal diameter primary connection | 3/4 inch (20) | Number of groups secondary | 11 |
| With valves on primary connection | ✔ | Outer pipe diameter secondary | 12\|20 Millimetre |
| With mixing valve | ✔ | Flow-through capacity | 0\|4.5 Litre per hour |
| Expandable | ✖ | Min. pressure difference secondary flow/return | 0 Kilo Pascal |
| Multi-zone manifold | ✖ | Width | 840 Millimetre |
| With temperature limit | ✔ | Height | 440 Millimetre |
| With non-return valve | ✔ | Depth | 190 Millimetre |
| With circulation pump | ✔ | | |
| Type of pump (system pump) | AC | | |
| Article compression class | PN 6 | | |
| With controller | ✔ | | |
| Hydraulic balance control | Static | | |
| Volume flow measurement | None | | |
| With thermometer | ✔ | | |
| Temperature measurement supply | Analogue | | |
| Temperature measurement return | Analogue | | |
| With de-aeration | ✔ | | |
| With pressure gauge | ✖ | | |
| Secondary connection | Euroconus standardless | | |
| Nominal diameter secondary connection | 3/4 inch (20) | | |
| Closable groups | ✔ | | |
| With flow-through indicator | ✖ | | |
| With thermal actuator | ✖ | | |
| With wall-mounting bracket | ✔ | | |
| With casing | ✖ | | |

## Related products