18EK05-03: Straight adapter manifold 3/8"

Commercial information

Adapter - 3/8” female for appendages with eurocone connector

- Extra adapter for the Henco PVDF manifold offers the possibility to equip the installation with an air vent
- Made from high-quality, lead-free brass alloy CW724
- Corrosion-resistant, stress corrosion-free

Certificates

QB (CSTBat), DVGW Wasser, ETA, KIWA, ÖVGW Wasser, SINTEF, SITAC, WRAS, KOMO, STF, GOST-R, TSU, EMI

Applications

Potable water, Heating, Cooling, Sanitary

Solutions

Building installations, Industry, Utility

Technical characteristics

Material connection 1	Polyvinylidene fluoride (PVDF)	Bend radius	0	Millimetre
Surface protection connection 1	Untreated	Length	31.5	Millimetre
Surface treatment connection 1	Untreated	Medium temperature (continuous)	-10|70	Degrees celsius
Material connection 2	Brass	Max. operating pressure at 20 °C	16	Bar
Surface protection connection 2	Untreated	Standard Dimension Ratio (SDR)	0	
Surface treatment connection 2	Untreated			
Shape	Straight			
Reducing	✖			
Eccentric	✖			
System specific	✔			
Connection 1	Euroconus (expired)			
Nominal diameter connection 2	3/8 inch (10)			
Connection 2	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)			
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)			
With buffer stud	✖			
High tensile strength	✖			
With thermal insulation	✖			
Ring stiffness class	Other			
With sealing rings/gaskets	✖			
Capped	✖			
With connection indicator	✖			
With drain valve	✖			
With de-aerator	✖			
FM quality mark	✖			
LPCB quality mark	✖			
ULC quality mark	✖			
UL quality mark	✖			
DIN-CERTCO certificate	✖			
VdS quality mark	✖			
With approval for TÜV	✖			
DVGW quality mark for gas	✖			
DVGW quality mark for water	✔			
KIWA certified	✔			
Gastec QA mark	✖			
KOMO certified	✔			
Type approval according to BBR/EKS	✖			

Related products