

Area of Application:
Wall mounted
Special water

Max working pressure 10bar at 20°C / 6bar at 65°C
Temperature range 5°C-65°C

Details:
Diaphragm headwork, open/close 1,5x360°
3-Zone colour. acc. to EN13792:2002

Removable nozzle

Materials in media contact:
Rubber, EPDM
PVDF
PTFE

Mounting:
½" nut with locking pins, O-ring and washer (See 94G0232)

Inlet / outlet connection:
ISO 7/1 - R3/8"
DIN 12 898 hose nozzle

Metal handle

60

200

1000

Ø10 /Ø7 PVDF hose

Removable
PVDF nozzle

ISO 7/1 - 3/8"

MEDIA CODE XX FOR SPECIAL WATER
ONE MEDIA FITTING
*Model shown for WDI

Media	Media description	Media code XX
WDI	Distilled water	03
WDC	Demineralized water	36

Description:

1-Valve, Wall mounted, 1-Hole, ,

Media:
Special water

Comments:

Drawing type:
Customer drawing

Weight:
0.839 Kg

Rev. Pos. Date TM No. Design by Drawn by: Change:

Designed by: Drawn by: Released on TM No. Date (DD-MM-YY):
BJP 20-08-2013

BROEN-LAB

This drawing is our property and cannot be given to a third party, copied or otherwise used without our permission. BROEN-LAB A/S.

Format: Drawing No.:
A3 253303510XX-09