



Spot EcoMax

- Fixed spotlight range with universal 68 mm cut-out
- Direct replacement for majority of halogen spotlights
- IP44 on light emitting side
- Can be used in e.g
- bathrooms and related environments



Specifications

Item Code	Item Description	Equivalent to (W)	Power (W)	Lumen	Efficacy (lm/W)	CCT (K)	Beam angle	Weight (kg/pc)
140055457	LEDSpotRF-E 7W-2700-36D-AL	Halogen 50W	7	510	73	2700	36°	0.08

Accessories



542098030700
Junction-Box-WH

Packaging Information

Item		Box			
Item Code	Item Description	Dimensions (mm) (LxWxH)	Gross Weight (kg)	EAN	pc/box
140055457	LEDSpotRF-E 7W-2700-36D-AL	100x100x48	0.12	6956321879587	1
542098030700	Junction-Box-WH	43x103.4x26	0.07	6941408868684	1

Technical Specifications

Lifetime (L70)	30,000 h
Lifetime (L80)	20,000 h
On-/Off-cycles	100,000
Colour consistency (SDCM)	4
Dimmability	On-Off
Finishing	Brushed aluminum front, matte black back
Colour rendering index CRI	≥ 80
Degree of protection (IP)	IP44
IP recessed part	n/a
Impact strength	IK02
Protection class	II
Risk group (EN 62471)	RG1
With control gear	Yes
Glow wire test	850°C
Driver failure rate (at 5,000 hrs)	1 %
Power factor	≥ 0.9

Electrical Supply

Frequency	50/60 Hz
Nominal voltage	220-240 V AC
DC input voltage	See catalogue Technical Data section
230V Cable length	0.3 m

Mechanical Properties

Material housing	Aluminium
Optical material	Polycarbonate

Ambient Conditions



Operating temperature	-25~+40°C
Application temperature	+25°C
Storage environment	-25~+50°C

3 YEARS WARRANTY




Dimensional Drawing (mm)

LEDSpotRF-E 7W



Photometric Data



Installation Opening Drawing (mm)

