
FBSS FLAT BUSBAR SUPPORT

CATALOG NUMBER

FBSS32X5



CERTIFICATIONS

FEATURES


- Supports busbars at an angle for easy connections
- Includes mounting holes for direct fixing of protection screen
- Adjustable arms for easy mounting
- Three phase with neutral circuit
- Halogeenvrij


PRODUCTKENMERKEN

- Article Number: 551190
- Material: Steel;Glass Fibre Reinforced Polyamide;Aluminum
- Max Working Voltage, IEC (Ui): 1000;1500
- Working Temperature: -40 tot 130 °C
- Typical Application Current Rating: 400 A
- Flammability Rating: UL® 94V-0
- Busbar Width: 32 mm
- Busbar Thickness: 5 mm
- Complies With: IEC® 60695-2-11 (gloeidraadtest 960 °C)
- Height: 47 mm
- Width: 338 – 390 mm

A: 325 – 377 mm
B: 290 mm
C: 65 mm
X: 6,5 x 23 mm
Unit Weight: 0,32 kg

DIAGRAMS





WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. U kunt de poductinformatiebladen downloaden van www.nvent.com of opvragen bij uw nVent-klantenservice. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en materiële schade veroorzaken en/of uw garantie ongeldig maken.

Noord-Amerika
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.