T5 Standard Short

F6W/T5/54-765

0000011



Product features

- T5 Standard Short

PRODUCT OVERVIEW

Product name	F6W/T5/54-765
Technology	Fluorescent
Watt (Rated) (W)	5.80
Lamp shape	Tubular shape
Type	T5 Standard Short
Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4942320
Luminous flux (lm)	240
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	41
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	75
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	Not applicable
Wattage (W)	6.00
Product Voltage (V)	42
Dimmable	Yes
Average life (Nominal) (h)	10000
Product EAN number	5410288000114

DATA TABLE

General data

Product name	F6W/T5/54-765
Technology	Fluorescent
Watt (Rated) (W)	5.80
Lamp shape	Tubular shape
Type	T5 Standard Short
Cap/Base	G5
Lamp finish	Frosted/Coated

© Feilo Sylvania | Date Printed: 04 Nov 2021

T5 Standard Short

F6W/T5/54-765

0000011

Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000108
E-number FI	4942320

Optical data

Luminous flux (lm)	240
Luminous flux (Rated) (lm)	240
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	41
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	6500
Light colour	Daylight
Colour Code	765
CRI (Ra)	75
Colour Variation Initial (SDCM)	SDCM5
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 2000 h 50Hz	0.88
Rated lumen maint. factor (%) at 4000 h 50Hz	0.82
Rated lumen maint. factor (%) at 6000 h 50Hz	0.78
Rated lumen maint. factor (%) at 8000 h 50Hz	0.75

Electrical data

Wattage (W)	6.00
Current (A)	0.160
Product Voltage (V)	42
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Drive current (mA)	160
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	7

Lifetime data

Average life (Nominal) (h)	10000
Average life (Rated) (h)	10000
Rated survival factor (%) at 2000 h 50Hz	1.00
Rated survival factor (%) at 4000 h 50Hz	0.99
Rated survival factor (%) at 6000 h 50Hz	0.96
Rated survival factor (%) at 8000 h 50Hz	0.83

Physical data

Nominal Product Length (mm)	225.0
Nominal Product Diameter (mm)	16

© Feilo Sylvania | Date Printed: 04 Nov 2021

T5 Standard Short

F6W/T5/54-765

0000011

Max. Length base to base (mm) - A	212.1
Length base to pin Min-Max (mm) - B	216.8-219.2
Max. Lamp Length (mm) - C/L	226.3
Max. Lamp Diameter (mm) - D	17.0
Weight (kg)	0.019


Packaging

Single packaging type	Carton
Product EAN number	5410288000114
Packaging single length / height (cm)	22.63
Packaging single width (cm)	1.87
Packaging single depth (cm)	1.9
DUN14 (inner)	25410288000118
Units per inner package	25
Packaging inner length / height (cm)	9.83
Packaging inner width (cm)	24.5
Packaging inner depth (cm)	9.97
DUN14 (outer)	15410288000111
Units per outer package	500
Packaging outer length / height (cm)	41.2
Packaging outer width (cm)	51.0
Packaging outer depth (cm)	25.2


Safety data

Lamp mercury content (mg)	2.30
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Suitable for household illumination	Yes

PHOTOMETRY



TECHNICAL DRAWINGS



© Feilo Sylvania | Date Printed: 04 Nov 2021

SYLVANIA

T5 Standard Short

F6W/T5/54-765

0000011



© Feilo Sylvania | Date Printed: 04 Nov 2021

SYLVANIA

T5 Standard Short

F6W/T5/54-765

0000011



© Feilo Sylvania | Date Printed: 04 Nov 2021