

Instar Eco Kit LED - Adjustable

INSTAR ECO KIT LED ADJ BA 36° 2700K

3079356



Range features

- IP23 Accent downlight perfect for 50W Halogen retrofits. 25° tiltable, Optimal solution in size and luminous efficiency for hospitality accent and display lighting applications. The Eco Kit also comes including a Non dimmable driver



PRODUCT OVERVIEW

Technology	LED
Ordering number	3079356
Average life (Rated) (h)	30000
EAN code	8711971793564
Mount	Ceiling recessed
Housing	Aluminium
LOR (%)	1
Beam angle(°)	36
Colour temperature (K)	2700
Luminous flux (lm)	450
Voltage (V)	220-240
Colour	Brushed Aluminium
IP rating	23
IK rating	2

Instar Eco Kit LED - Adjustable

INSTAR ECO KIT LED ADJ BA 36° 2700K

3079356

DATA TABLE

General data

Ordering number	3079356
Technology	LED
Average life (Rated) (h)	30000
EAN code	8711971793564
Mount	Ceiling recessed
Range features	IP23 Accent downlight perfect for 50W Halogen retrofits. 25° tiltable, Optimal solution in size and luminous efficiency for hospitality accent and display lighting applications. The Eco Kit also comes including a Non dimmable driver
Product name	INSTAR ECO KIT LED ADJ BA 36° 2700K
Control gear availability	Electronic
Control gear type	External
Environment	Interior
General application	Indoor Lighting, Hospitality and Accent lighting, Reception rooms, lobbies, corridors, bathrooms, changing rooms
Housing	Aluminium
Sales pack quantity	1

Optical data

LOR (%)	1
Beam angle(°)	36
Colour temperature (K)	2700
Luminous flux (lm)	450
Distribution type	Direct
Optical system	Bright Aluminium Reflector

Electrical data

Total power consumption (W)	10
Voltage (V)	220-240
Drive current (mA)	800mA
Electrical protection	CLASS II

Instar Eco Kit LED - Adjustable

INSTAR ECO KIT LED ADJ BA 36° 2700K

3079356

Physical data

Weight (kg)	0.28
Colour	Brushed Aluminium
Lamp included	Integrated LED
Height (mm)	62mm
Width (mm)	78mm
Length (mm)	78mm
IP rating	23
IK rating	2
Cutout diameter (mm)	68mm x 68mm
Recessed depth (mm)	100mm
Diffuser finish	Clear
Diffuser material	Glass
Reflector finish	Bright Aluminium Reflector
Safety distance	110mm
Single package dimensions (L x W x H) (cm)	14.00 x 10.00 x 8.50
Outer package dimensions (L x W x H) (cm)	52.00 x 30.00 x 44.50

Instar Eco Kit LED - Adjustable

INSTAR ECO KIT LED ADJ BA 36° 2700K

3079356

PHOTOMETRY

