


PIR Detectors - Ceiling-mounted

Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override

0041540



Product features

- PIR sensor with switching capability. On/off switching via lux sensing. Dual sensitivity. Absence/presence detection. Adjustable time delay (10sec to 99min). Up to 7m detection radius at 2.8m mounting height. Programmable via handset. Mounting accessories available. Can be connected in parallel for larger areas and L-shaped corridors. Up to 10A load.



PRODUCT OVERVIEW

Product name	Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000533
IP rating	IP40
Product EAN number	5410288415406
Max load (A)	10
Input	PIR, IR, Lux
Input protocol	PIR Sensor, IR Signal, Lux sensor
Output protocol	Switched
Number of channels	1

DATA TABLE

General data

Product name	Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override
Technology	Controls
Mount	Ceiling recessed mounting, Ceiling surface mounting
Environment	Interior
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Operating temperature range (°C)	-10°C - 35°C
ETIM Class	EC000533

Electrical data

Mains voltage (V)	220-240V~
Mains frequency (Hz)	50

PIR Detectors - Ceiling-mounted

Compact PIR presence/absence detector with lux level sensing. time delay function and infrared override

0041540

Physical data

IP rating	IP40
Nominal Product Length (mm)	76
Nominal Product Width (mm)	76
Nominal Product Height (mm)	68.5
Cutout Dimensions (W x L in mm or Diameter in mm)	64
Weight (kg)	0.105
Recessed Depth (mm)	65

Packaging

Single packaging type	Carton
Product EAN number	5410288415406
Packaging single length / height (cm)	9.5
Packaging single width (cm)	9.5
Packaging single depth (cm)	7.5
Units per outer package	100
Packaging outer length / height (cm)	47.0
Packaging outer width (cm)	47.0
Packaging outer depth (cm)	52.0

Safety data

Optimal operating condition (°C)	-10-35
----------------------------------	--------

TECHNICAL DRAWINGS

