

Instar Eco kit LED White 36o 2,700K Adjustable Dimmable

3079455



Range features

- IP23 Accent downlight perfect for 50W Halogen retrofits. 25° tiltable, Optimal solution in size and luminous efficiency for hospitality accent and display lighting applications. The Eco Kit also comes including a Non dimmable driver



PRODUCT OVERVIEW

Ordering number	3079455
Technology	LED
Average life (Rated) (h)	30000
Compatible dimmers	Leading / Trailing Edge
Mount	Ceiling recessed
Housing	Aluminium
LOR (%)	1
Beam angle(°)	36
Colour temperature (K)	2700
Luminous flux (lm)	450
Voltage (V)	220-240
Colour	White
IP rating	23
IK rating	2

Instar Eco kit LED White 36o 2,700K Adjustable Dimmable

3079455

DATA TABLE

General data

Technology	LED
Ordering number	3079455
Average life (Rated) (h)	30000
Compatible dimmers	Leading / Trailing Edge
Mount	Ceiling recessed
Range features	IP23 Accent downlight perfect for 50W Halogen retrofits. 25° tiltable, Optimal solution in size and luminous efficiency for hospitality accent and display lighting applications. The Eco Kit also comes including a Non dimmable driver
Product name	Instar Eco kit LED White 36o 2,700K Adjustable Dimmable
Control gear availability	Electronic
Control gear type	External
Environment	Interior
General application	Indoor Lighting, Hospitality and Accent lighting, Reception rooms, lobbies, corridors, bathrooms, changing rooms
Housing	Aluminium

Optical data

LOR (%)	1
Beam angle(°)	36
Colour temperature (K)	2700
Luminous flux (lm)	450
Distribution type	Direct
Optical system	Bright Aluminium Reflector

Electrical data

Total power consumption (W)	10
Voltage (V)	220-240
Drive current (mA)	800mA
Electrical protection	CLASS II

Instar Eco kit LED White 36o 2,700K Adjustable Dimmable


3079455

Physical data

Colour	White
Lamp included	Integrated LED
Height (mm)	62mm
Width (mm)	78mm
Length (mm)	78mm
IP rating	23
IK rating	2
Cutout diameter (mm)	68mm x 68mm
Recessed depth (mm)	100mm
Diffuser finish	Clear
Diffuser material	Glass
Reflector finish	Bright Aluminium Reflector
Safety distance	110mm

Instar Eco kit LED White 360 2,700K Adjustable Dimmable 3079455

PHOTOMETRY



TECHNICAL DRAWINGS

