F8wt5/133 25way Emergency

0001912

Range features



CE

PRODUCT OVERVIEW

Light colour	640 Cool White
Ordering number	0001912
Technology	Fluorescent
Energy class	
Lamp shape	Linear
Lamp finish	Coated
Dimmable	
Cap/Base	G5
Type	T5 Emergency
EAN code	5410288019123
CRI (Ra)	60
Colour temperature (K)	4000
Luminous flux (Rated) (lm)	
Watt (Nominal) (W)	8
Voltage (V)	71

F8wt5/133 25way Emergency

0001912

DATA TABLE

General data

Ordering number	0001912
Technology	Fluorescent
Average life (Nominal) (h)	8000
Energy class	
Lamp finish	Coated
Lamp shape	Linear
Dimmable	
Cap/Base	G5
Type	T5 Emergency
EAN code	5410288019123
Product name	F8w t5/133 25w ay Emergency
Lamp mercury content (mg)	2.3
Control gear required	Yes
Fixture rating	Open
IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
IEC Reference 3	
Intended purpose	
Special purpose lamp	Yes
Transformer required	No
Sales pack quantity	25
Rated survival factor at 2000 h 50Hz	
Rated survival factor at 4000 h 50Hz	
Rated survival factor at 6000 h 50Hz	
Rated survival factor at 8000 h 50Hz	
Rated survival factor at 12000 h 50Hz	
Rated survival factor at 16000 h 50Hz	
Rated survival factor at 20000 h 50Hz	

F8wt5/133 25way Emergency

0001912

Optical data

Light colour	640 Cool White
CRI (Ra)	60
Colour temperature (K)	4000
Luminous flux (Rated) (lm)	
Luminous flux (Nominal) at 35°C (lm)	
Luminous flux (Nominal) (lm)	
Ambient temperature for maximum luminous flux (°C)	
Rated lumen maint. factor at 2000 h 50Hz	
Rated lumen maint. factor at 4000 h 50Hz	
Rated lumen maint. factor at 6000 h 50Hz	
Rated lumen maint. factor at 8000 h 50Hz	
Rated lumen maint. factor at 12000 h 50Hz	
Rated lumen maint. factor at 16000 h 50Hz	
Rated lumen maint. factor at 20000 h 50Hz	

Electrical data

kWh per 1000 hours burning time	
Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.	
Watt (Rated) (W)	
Watt (Nominal) (W)	8
Voltage (V)	71
Ignition voltage (V)	
Current (A)	0.04

Physical data

Weight (kg)	0.02
Length base to base (mm) - A	288.3
Length base to pin Min-Max - B	293.0-295.4
Max overall length (mm) - C	302.5
Max. Lamp Diameter (mm) - D	16
Diameter (mm)	16
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	30.30 x 1.90 x 1.90
Outer package dimensions (L x W x H) (cm)	32.00 x 11.00 x 10.50

F8wt5/133 25way Emergency

0001912

TECHNICAL DRAWINGS

