T5 FHO Luxline® Plus

FHO 24W/T5/840

0002773



Range features

PRODUCT OVERVIEW

Light colour	840 Cool White
Technology	Fluorescent
Ordering number	0002773
Energy class	A
Lamp shape	Linear
Lamp finish	Coated
Dimmable	
Cap/Base	G5
Type	T5 FHO Luxline Plus
EAN code	5410288027739
CRI (Ra)	85
Colour temperature (K)	4000
Luminous flux (Rated) at 25°C (lm)	1750
Efficacy (Rated) at 25°C (lm/w)	74
Watt (Nominal) (W)	24
Voltage (V)	75

T5 FHO Luxline® Plus

FHO 24W/T5/840

0002773

DATA TABLE

General data

Ordering number	0002773
Technology	Fluorescent
Average life (Nominal) (h)	24000
Energy class	A
Lamp finish	Coated
Lamp shape	Linear
Dimmable	
Cap/Base	G5
Type	T5 FHO Luxline Plus
EAN code	5410288027739
Product name	FHO 24W/T5/840
Lamp mercury content (mg)	2.3
Control gear required	Yes
Fixture rating	Open
IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
IEC Reference 3	
Intended purpose	General lighting
Special purpose lamp	No
Transformer required	No
Rated survival factor at 2000 h 50Hz	0.99
Rated survival factor at 4000 h 50Hz	0.98
Rated survival factor at 6000 h 50Hz	0.96
Rated survival factor at 8000 h 50Hz	0.94
Rated survival factor at 12000 h 50Hz	0.93
Rated survival factor at 16000 h 50Hz	0.9
Rated survival factor at 20000 h 50Hz	0.84

T5 FHO Luxline® Plus

FHO 24W/T5/840

0002773

Optical data

Light colour	840 Cool White
CRI (Ra)	85
Colour temperature (K)	4000
Luminous flux (Rated) at 25°C (lm)	1750
Luminous flux (Nominal) at 35°C (lm)	1950
Luminous flux (Nominal) at 25°C (lm)	1750
Ambient temperature for maximum luminous flux (°C)	35
Rated lumen maint. factor at 2000 h 50Hz	0.97
Rated lumen maint. factor at 4000 h 50Hz	0.95
Rated lumen maint. factor at 6000 h 50Hz	0.93
Rated lumen maint. factor at 8000 h 50Hz	0.92
Rated lumen maint. factor at 12000 h 50Hz	0.91
Rated lumen maint. factor at 16000 h 50Hz	0.9
Rated lumen maint. factor at 20000 h 50Hz	0.88

Electrical data

kWh per 1000 hours burning time	26
Efficacy (Rated) at 35°C (lm/w)	74
Efficacy (Rated) at 25°C (lm/w)	74
Watt (Nominal) (W)	24
Watt (Rated) - High frequency (W)	23.5
Watt (Rated) (W)	23.5
Voltage (V)	75
Ignition voltage (V)	0
Current (A)	0.3

Physical data


Length base to base (mm) - A	549
Length base to pin Min-Max - B	553.7-556.1
Max overall length (mm) - C	563.2
Max. Lamp Diameter (mm) - D	16
Diameter (mm)	16

T5 FHO Luxline® Plus


FHO 24W/T5/840


0002773

PHOTOMETRY



TECHNICAL DRAWINGS





ENERGY LABEL

