

Insaver LED 75 - Round - White bezel

Insaver 75 LED RS WW DB WH

3097100



Range features

- Innovative downlight with square and round designs using array chip technology. High colour rendering index (CRI). Thermal management ensures service life up to 50.000 hrs. Low power consumption - 16W (Full power consumption of luminaire including driver).



PRODUCT OVERVIEW

Light colour	Warm w hite
Ordering number	3097100
Technology	LED
Average life (Rated) (h)	50000
EAN code	8711971971009
Certifications	CE
Mount	Recessed
Housing	Aluminium
CRI (Ra)	80
Beam angle(°)	55
Colour temperature (K)	3000
Luminous flux (lm)	888
Efficacy (Rated) (lm/w)	55.5
Voltage (V)	220-240
Colour	White
IP rating	65
IK rating	2

Insaver LED 75 - Round - White bezel

Insaver 75 LED RS WW DB WH

3097100

DATA TABLE

General data

Technology	LED
Ordering number	3097100
Average life (Rated) (h)	50000
EAN code	8711971971009
Certifications	CE
Mount	Recessed
Range features	Innovative downlight with square and round designs using array chip technology. High colour rendering index (CRI). Thermal management ensures service life up to 50.000 hrs. Low power consumption - 16W (Full power consumption of luminaire including driver).
Product name	Insaver 75 LED RS WW DB WH
Control gear type	Dimmable (leading/trailing edge)
Environment	External (remote)
General application	Indoor illumination, corridors, offices, reception rooms
Housing	Aluminium

Optical data

Light colour	Warm white
CRI (Ra)	80
Beam angle(°)	55
Colour temperature (K)	3000
Luminous flux (lm)	888
Distribution type	Direct - symmetrical

Electrical data

Efficacy (Rated) (lm/w)	55.5
Total power consumption (W)	16
Voltage (V)	220-240
Drive current (mA)	350
Electrical protection	Class II
Glow wire test	N/S

Insaver LED 75 - Round - White bezel

Insaver 75 LED RS WW DB WH

3097100

Physical data

Weight (kg)	0.4
Colour	White
Lamp included	Integrated LED
Height (mm)	65
Width (mm)	90
Length (mm)	90
IP rating	65
IK rating	2
Cutout diameter (mm)	75 x 75
Cutout shape	Round
Diffuser finish	Clear
Diffuser material	Glass
Reflector finish	Facetted aluminium refelctor

ENERGY LABEL

