SIEMENS

Data sheet 5TT4125-0



Remote control switch with 1 NO contact, and 1 NC with central ON/OFF function
Contact for 230 V AC, 400V 16A Control 230 V AC

Model	
product brand name	SENTRON
product designation	Remote control switch
latching relay design	mechanical for central control
General technical data	
electrical endurance (operating cycles)	50 000
galvanic isolation between magnet coil and contact	Yes
switching voltage of the contacts at AC minimum	10 V
switching current at AC per contact minimum	100 mA
power loss [V·A] of magnet coil with pulse rated value	7 VA
Voltage	
type of voltage of the operating voltage	AC
continuous voltage fuse version	Yes
operating range factor control supply voltage rated value at AC at 50 Hz	
● initial value	0.8
● full-scale value	1.1
surge voltage resistance rated value	4 kV
supply voltage	250 V
Supply voltage	
supply voltage minimum	250 V
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity apparent power	
● for fluorescent lamp load with DUO circuit	700 VA
● for fluorescent lamp load with parallel compensation	300 VA
● for uncompensated fluorescent lamp load	400 VA
switching capacity current	
● at cos phi 0.6	16 A
● rated value	16 A
switching capacity active power with incandescent lamp load	2 000 W
Dissipation	
power loss [W]	
● at 16 A per contact rated value	1.2 W
● of magnet coil with pulse rated value	4.5 W
Control current	
type of voltage	
● of control voltage_1	AC
● of control voltage_2	AC

Subject to change without notice
© Copyright Siemens

control voltage	
• _1 initial value	184 V
• _1 full-scale value	253 V
• _1 setpoint	230 V
• _2 initial value	184 V
• _2 full-scale value	253 V
• _2 setpoint	230 V
control voltage frequency	
• _1 initial value	50 Hz
• _1 full-scale value	50 Hz
• _2 initial value	50 Hz
• _2 full-scale value	50 Hz
operating range factor of control voltage_2	0.8
Product details	
product component switch position indicator	Yes
number of NC contacts	1
number of NO contacts	1
number of CO contacts	0
Product function	
product function direct operation	Yes
pulse duration minimum	50 ms
Number	
number of terminals	8
Connections	
connectable conductor cross-section for flexible conductor with core end processing	
• minimum	1 mm²
• maximum	6 mm²
connectable conductor cross-section for rigid conductor	
• minimum	1 mm²
• maximum	6 mm²
tightening torque with screw-type terminals	
• minimum	0.8 N·m
• maximum	1 N·m
Mechanical Design	
width of opening of the contacts	1.2 mm
mounting height	90 mm
installation depth	70 mm
number of modular width units	1.5
fastening method	DIN rail
mounting position	any
required spacing for live parts	6 mm
net weight	165 g
Environmental conditions	
ambient temperature during operation	
• minimum	-10 °C
• maximum	40 °C

General Product Approval | **Declaration of Conformity**

Confirmation | Miscellaneous

Test Certificates	other		Environment
Miscellaneous	Confirmation	Miscellaneous	Environmental Confirmations

Subject to change without notice
© Copyright Siemens

Further information

Siemens has decided to exit the Russian market (see here).
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/lowvoltage/catalogs


Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4125-0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5TT4125-0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4125-0

CAx-Online-Generator
http://www.siemens.com/cax

Tender specifications
http://www.siemens.com/specifications



last modified: 8/15/2023

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens