SIEMENS

Data sheet 3RK1107-0BE00-2AA2



AS-i SlimLine Compact module SC22.5, IP20, analog 2AQ-C/V screw terminals 2 x analog output outputs switchable C/V overall width 22.5 mm

product designation	Slimline Compact I/O module for use in the control cabinet
design of the product	AS-i SC22.5, 2AQ voltage/current
General technical data	
protection class IP	IP20
design of the slave type	standard slave
AS-Interface slave profile	S-7.3.5
ID1 code	F; Factory setting, changeable
operating voltage according to AS-Interface specification	18 ... 31.6 V
product function suitable for AS-i Power24V	Yes
protocol is supported AS-Interface protocol	Yes
consumed current from profile conductors of the AS-Interface	
● at 30 V maximum	200 mA
● at 24 V with AS-i Power24V maximum	200 mA
type of address setting of AS-i slaves	via front addressing socket
display version	
● for AS-Interface	LED green/red
reference code	
● according to EN 61346-2	K
● according to DIN 40719 extended according to IEC 204-2 according to IEC 750	A
shock resistance	15g / 11 ms (modules) or 10g / 11 ms (modules with device connector)
other information	An auxiliary external feed (AUX POWER) of between 20 and 30 V DC is necessary for supplying the output circuits. The auxiliary feed must comply with IEC 60990 (PELV), protection class III.
Digital Inputs	
number of digital inputs	0
number of digital inputs safety-related	0
Digital Outputs	
number of digital outputs	0
type of voltage supply at the outputs	AS interface or U_AUX
Analog inputs	
number of analog inputs	0
A/D resolution for analog inputs/outputs	12 bit
Analog outputs	
number of analog outputs	2
signal range at analog output	0 ... 20 mA; 4 ... 20 mA; +/- 20 mA; 1 ... 5 V; 0 ... 10 V; +/- 10 V
product function parameterizable output variable	Yes
Errors/ accuracies	
relative symmetrical operational limit relating to input range/output range	1 %; full sclae

Subject to change without notice
© Copyright Siemens

relative symmetrical basic error limit relating to input range/output range at 25 °C	0.8 %
symmetrical temperature error per K relating to input range/output range	0.01 %/K
relative symmetrical linearity error relating to input range/output range	0.08 %
relative symmetrical repeat accuracy relating to input range/output range in settled state 25 °C	0.1 %
Device connector	
ampacity of the interface to the device connector	
● for AS-Interface	2 A
● for external auxiliary voltage	4 A
Installation/ mounting/ dimensions	
fastening method	screw and snap-on mounting
height	100 mm
width	22.5 mm
depth	120 mm
Ambient conditions	
ambient temperature	
● during operation	-25 ... +70 °C
● during storage	-40 ... +85 °C
Connections/ Terminals	
type of electrical connection of the inputs and outputs	Screw terminals
type of connectable conductor cross-sections	
● solid	1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.5 mm²)
● finely stranded with core end processing	1x (0.25 ... 2.5 mm²), 2x (0.25 ... 1.0 mm²)
● finely stranded without core end processing	Not permitted
● for AWG cables solid	1x (24 ... 14), 2x (24 ... 16)
● for AWG cables stranded	Not permitted

Certificates/ approvals

General Product Approval				EMC	Declaration of Conformity
CCC	Confirmation	UL	EAC	RCM	EG-Konf.

Declaration of Conformity	Test Certificates	Marine / Shipping			
UKCA	Type Test Certificates/Test Report	DNV	LRS	PRS	DNV·GL

other	
ASi	Confirmation

Further information

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).
Siemens has decided to exit the Russian market (see here).
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business
Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)


Subject to change without notice
© Copyright Siemens

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1107-0BE00-2AA2


Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1107-0BE00-2AA2

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK1107-0BE00-2AA2

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1107-0BE00-2AA2&lang=en



Subject to change without notice
© Copyright Siemens



last modified: 8/11/2023

Subject to change without notice
© Copyright Siemens