



circuit breaker 3VA5 UL frame 125 breaking capacity class M 35kA @ 480 V 3-pole, line protection TM210, FTFM, In=70A overload protection Ir=70A fixed short-circuit protection Ii=10 x In UL 489 SB (naval), 50° C without connection

| Model                                                                                                                      |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SENTRON                     |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | MEAM                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the load switch / according to UL 489 / High-Intensity-Discharge circuit breaker (HID Type)                      | No                          |
| design of the load switch / according to UL 489 / Switching Duty circuit breaker (SWD Type)                                | No                          |
| design of the overcurrent release                                                                                          | TM210                       |
| protection function of the overcurrent release                                                                             | LI                          |
| number of poles                                                                                                            | 3                           |
| General technical data                                                                                                     |                             |
| operating voltage / at AC / rated value                                                                                    | 690 V                       |
| power loss [W] / maximum                                                                                                   | 18.3 W                      |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 6.1 W                       |
| mechanical service life (operating cycles) / typical                                                                       | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 8 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 4 000                       |
| electrical endurance (operating cycles) / at 480 V                                                                         | 8 000                       |
| electrical endurance (operating cycles) / at 600 V                                                                         | 4 000                       |
| product feature / for neutral conductors / upgradable/retrofittable / short-circuit and overload proof                     | No                          |
| ground-fault monitoring version                                                                                            | without                     |
| product function                                                                                                           |                             |
| • communication function                                                                                                   | No                          |
| • other measurement function                                                                                               | No                          |
| Net Weight                                                                                                                 | 0.88 kg                     |
| Current                                                                                                                    |                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | No                          |
| operational current                                                                                                        |                             |
| • at 40 °C                                                                                                                 | 70 A                        |
| • at 45 °C                                                                                                                 | 69 A                        |
| • at 50 °C                                                                                                                 | 68 A                        |
| • at 55 °C                                                                                                                 | 67 A                        |
| • at 60 °C                                                                                                                 | 66 A                        |
| • at 65 °C                                                                                                                 | 65 A                        |
| • at 70 °C                                                                                                                 | 64 A                        |

|                                                                                          |                                                                                                                                                                |
|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Switching capacity according to IEC 60947</b>                                         |                                                                                                                                                                |
| switching capacity class of the circuit breaker                                          | M                                                                                                                                                              |
| design of short-circuit protection                                                       | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |
| <b>Switching capacity according to UL 489</b>                                            |                                                                                                                                                                |
| current breaking capacity                                                                |                                                                                                                                                                |
| • at 240 V                                                                               | 85 kA                                                                                                                                                          |
| • at 480 V                                                                               | 35 kA                                                                                                                                                          |
| • at 600 Y/347 V                                                                         | 18 kA                                                                                                                                                          |
| <b>Adjustable parameters</b>                                                             |                                                                                                                                                                |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic |                                                                                                                                                                |
| • minimum                                                                                | 70 A                                                                                                                                                           |
| • maximum                                                                                | 70 A                                                                                                                                                           |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic     |                                                                                                                                                                |
| • minimum                                                                                | 1 s                                                                                                                                                            |
| • maximum                                                                                | 1 s                                                                                                                                                            |
| adjustable response value setting current (Ii) / for I-tripping                          |                                                                                                                                                                |
| • minimum                                                                                | 700 A                                                                                                                                                          |
| • maximum                                                                                | 700 A                                                                                                                                                          |
| adjustable setting current (InN) / for N-tripping                                        |                                                                                                                                                                |
| • minimum                                                                                | 0 A                                                                                                                                                            |
| • maximum                                                                                | 0 A                                                                                                                                                            |
| product function / grounding protection                                                  | No                                                                                                                                                             |
| <b>Mechanical Design</b>                                                                 |                                                                                                                                                                |
| product component                                                                        |                                                                                                                                                                |
| • undervoltage release                                                                   | No                                                                                                                                                             |
| • voltage trigger                                                                        | No                                                                                                                                                             |
| • trip indicator                                                                         | No                                                                                                                                                             |
| height [in]                                                                              | 5.51 in                                                                                                                                                        |
| height                                                                                   | 140 mm                                                                                                                                                         |
| width [in]                                                                               | 3 in                                                                                                                                                           |
| width                                                                                    | 76.2 mm                                                                                                                                                        |
| depth [in]                                                                               | 3.01 in                                                                                                                                                        |
| depth                                                                                    | 76.5 mm                                                                                                                                                        |
| <b>Connections</b>                                                                       |                                                                                                                                                                |
| arrangement of electrical connectors / for main current circuit                          | Without connection                                                                                                                                             |
| type of electrical connection / for main current circuit                                 | Without                                                                                                                                                        |
| <b>Auxiliary circuit</b>                                                                 |                                                                                                                                                                |
| number of CO contacts / for auxiliary contacts                                           | 0                                                                                                                                                              |
| <b>Accessories</b>                                                                       |                                                                                                                                                                |
| product extension / optional / motor drive                                               | Yes                                                                                                                                                            |
| <b>Environmental conditions</b>                                                          |                                                                                                                                                                |
| protection class IP / on the front                                                       | IP40                                                                                                                                                           |
| ambient temperature                                                                      |                                                                                                                                                                |
| • during operation / minimum                                                             | -25 °C                                                                                                                                                         |
| • during operation / maximum                                                             | 70 °C                                                                                                                                                          |
| • during storage / minimum                                                               | -40 °C                                                                                                                                                         |
| • during storage / maximum                                                               | 80 °C                                                                                                                                                          |
| <b>Approvals / Certificates</b>                                                          |                                                                                                                                                                |
| <b>General Product Approval</b>                                                          |                                                                                                                                                                |



[Confirmation](#)



General Product Approval

EMV

Test Certificates

Marine / Shipping



[Miscellaneous](#)



[Type Test Certificates/Test Report](#)



Marine / Shipping

other



[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA5170-5ED31-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA5170-5ED31-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA5170-5ED31-1AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA5170-5ED31-1AA0)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





